



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-162-S

To:	Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241	Bid Date:	2018-03-20
Attn.:	N/A	Expiry Date:	2018-04-19
Phone:	724-745-5300	Creator:	Drew Pomrenke , dpomrenke@jboconnor.com
		Sales Rep.:	Casey Devlin , cdevlin@jboconnor.com
		Shipping Address:	, Princeton, West Virginia, United States

Job Name: Mountain Valley Elementary School

Architect: ZMM Architects & Engineers

Comments:

Section Brand: Sloan

Label	Product No. Description	List Price	Qty.
P-1H	ST-2009 Sloan - Floor mounted china water closet, 1.28, 1.6/1.1 AND 1.6 GPF, elongated bowl with 1-1/2" IPS top spud. Standard height (2102009).	\$129.95	1
	ECOS 8111-1.6/1.1 Sloan - Battery-powered Flushometer, Sensor activated, 1.6/1.1 gpf/6.0/4.2 Lpf (3370400)	\$621.60	1
<i>Note: Spec 22 42 13-2 - Commercial Water Closets; P510 Plumbing Fixture Schedule</i>			
P-2H	ST-2309-A Sloan - Vitreous china univeral Junior Toilet bowl only, 1.28, 1.6/1.1 and 1.6 GPF, Floor mounted, Top supply, "baby bowl". (2102309)	\$206.90	1
	ECOS 8111-1.6/1.1 Sloan - Battery-powered Flushometer, Sensor activated, 1.6/1.1 gpf/6.0/4.2 Lpf (3370400)	\$621.60	1
<i>Note: Spec 22 42 13-2 - Commercial Water Closets; P510 Plumbing Fixture Schedule</i>			
P-3H	ST-2029 Sloan - Vitreous china, ADA compliant water closet bowl only, 1.28, 1.6/1.1 AND 1.6 gpf, Floor mounted elongated bowl with 1-1/2" IPS top spud inlet. 1,000 LB load tested (2102029)	\$154.45	1
	ECOS 8111-1.6/1.1 Sloan - Battery-powered Flushometer, Sensor activated, 1.6/1.1 gpf/6.0/4.2 Lpf (3370400)	\$621.60	1
<i>Note: Spec 22 42 13-2 - Commercial Water Closets; P510 Plumbing Fixture Schedule</i>			
P-4H	SU-1009-A Sloan - Universal Vireous china, 3/4" top spud. 0.125, 0.25 and 0.5 GPF includes dome strainer. (1101009)	\$262.30	1
	ECOS 8186-0.125 Sloan - Ecos electronic Battery powered, sensor activated, 3/4" top spud, exposed urinal flushometer. Courtesy flush override button. Requires no AC hookups, uses four AA batteries. Override button 0.13 GPF (3250325)	\$583.60	1
<i>Note: Spec 22 42 13.16-2 - Commercial Urinals; P510 Plumbing Fixture Schedule</i>			
P-5H/P-6H/P-12	SS-3003 Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$83.40	1

EBF-650

\$744.80 1

Sloan - Battery powered, chrome plated brass sensor operated 4" center-set electronic hand washing faucet for tempered or hot/cold water. .5 GPM vandal resistant spray head. (3315025)

Note: Spec 22 42 16.13-5 - Commercial Lavatories; P510 Plumbing Fixture Schedule

Note: Faucet model not specified, quoting suggestion subject to approval. Dims of basin quoted is larger than spec'd. Please be advised.

Section Brand: Elkay

Label	Product No. Description	List Price	Qty.
-------	----------------------------	------------	------

P-7	LR22192 Elkay - 18 Gauge Stainless Steel 22' x 19.5' x 7.625' Single Bowl Top Mount Kitchen Sink	\$805.00	1
-----	--	----------	---

	LK99 Elkay - DRAIN	\$114.00	1
--	------------------------------	----------	---

Note: Spec 22 42 13.16-3 - Commercial Lavatories; P510 Plumbing Fixture Schedule. Quoting suggested strainer.

P-8	LR22223 Elkay - 18 Gauge Stainless Steel 22' x 22' x 7.625' Single Bowl Top Mount Kitchen Sink	\$817.00	1
-----	--	----------	---

Note:

	LK99 Elkay - DRAIN	\$114.00	1
--	------------------------------	----------	---

Note: Spec 22 42 13.16-3 - Commercial Lavatories; P510 Plumbing Fixture Schedule. Please be advised, hole punching needs to be clarified.

Quoting suggested strainer.

P-9	LR22192 Elkay - 18 Gauge Stainless Steel 22' x 19.5' x 7.625' Single Bowl Top Mount Kitchen Sink	\$805.00	1
-----	--	----------	---

	LK99 Elkay - DRAIN	\$114.00	1
--	------------------------------	----------	---

Note: Spec 22 42 13.16-3 - Commercial Lavatories; P510 Plumbing Fixture Schedule

Quoting suggested strainer.

P-13	VRCHDTL8SC Elkay - T/L 14GA ADA VR COOLER	\$5,282.00	1
------	---	------------	---

Note: Spec 22 47 16-2 - Pressure Water Coolers; P510 Plumbing Fixture Schedule

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
-------	----------------------------	------------	------

P-5H/P-6H/P-7/P-9/P-10/P-11/P-12/P-14	LFLM495-1 Powers - 1/2 LFLM495-1	\$252.00	1
---------------------------------------	--	----------	---

Note: Spec 22 42 13.16-3 & Spec 22 42 13.16-4 - Commercial Lavatories; P510 Plumbing Fixture Schedule

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
-------	----------------------------	------------	------

RPBFP	LF909-OSY : 3 Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, UL/FM outside stem & yoke gate valve, flange connections, 3"Ø (76 mm) pipe connection (0122776)	\$7,751.00	1
-------	--	------------	---

	909-AGF Watts - 909-AGF Air Gap (0881378)	\$164.00	1
--	---	----------	---

LF777SI : 3	\$814.00	1
Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 3"Ø (76 mm) valve (0379118)		
<i>Note: P510 - Domestic Water Service Detail; Quoting as suggestion</i>		

OB-A/OB-B 2-M2DWB	\$161.50	1
Watts - brass body, 1/2" solder or compression connection, single lever, 3/4" hose connection outlets, 150 psi maximum pressure, 180° F maximum temperature, molded plastic enclosure with top and side knockouts, drain knock out to accommodate waste drain pipe (0006644 & 0006625)		
<i>Note: Spec 22 11 19-7 - Domestic Water Piping Specialties;</i>		
<i>Note: Finish in plastic in lieu of stainless steel</i>		

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
P-4H	CA-321 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$663.00	1

Note: Spec 22 42 13.16-2 - Commercial Urinals; P510 Plumbing Fixture Schedule

P-5H/P-6H	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$782.00	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,114.00	1

Note: Spec 22 42 16.13-3 - Commercial Lavatories; P510 Plumbing Fixture Schedule

P-8	SI-742 Watts - epoxy coated, cast aluminum body, gasketed cover, removable stainless steel sediment basket, 2" (51 mm) IPS threaded connections. 10" (254 mm) clearance required above cover to remove sediment bucket.	\$1,121.00	1
-----	---	------------	---

Note: Spec 22 42 16.13-3 - Commercial Lavatories; Spec 22 13 19-7 - Sanitary Waste Piping Specialties & P510 Plumbing Fixture Schedule

P-13	CA-431-1 Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.	\$960.00	1
------	---	----------	---

Note: Spec 22 47 16-1 - Pressure Water Coolers; P510 Plumbing Fixture Schedule

WH-A	HY-725-88 Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		
	HY-725-88,-6,-8 Watts - 6" (152 mm), 8" (203 mm) thick	\$1,222.00	1
	HY-725-88,-10,-12,-14 Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick	\$1,335.00	1

	HY-725-88,-16,-18	\$1,446.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	<i>Note: Spec 22 11 19-4 - Domestic Water Piping Specialties</i>		
WH-B	HY-330	\$1,015.00	1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, warm climate hydrant, all bronze head, seat casting and internal working parts, wall mount, concealed, integral vacuum breaker, nickel bronze box and door, chrome plated face, 6-7/16" x 5-7/16" (164 mm x 138 mm), loose key		
	<i>Note: Spec 22 11 19-4 - Domestic Water Piping Specialties;</i>		
	<i>Note: Quoting as an alternate, Watts does not have an equal alternate to the valve specified.</i>		
WH-C	HY-450	\$1,066.00	1
	Watts - warm climate, heavy duty chrome plated bronze head, seat casting and internal working parts, wall mount, concealed, polished chrome plated face plate, vandal resistant integral vacuum breaker, 6-7/16" x 5-7/16" (164 mm x 138 mm), chrome plated face, nickel bronze box and door, loose key, 3/4"Ø (19 mm) male hose connection, 1" male threaded x 3/4" internal SWT 90° connection with 360° swivel.		
	<i>Note: Spec 22 11 19-4 - Domestic Water Piping Specialties;</i>		
WHA (Belows Type)	SS Series		
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$434.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$884.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,321.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$3,313.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$3,740.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$4,596.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
	<i>Note: Spec 22 11 19-6 - Domestic Water Piping Specialties;</i>		
RF	HY-900	\$2,497.00	1
	Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, roof hydrant with and lift handle and lock option, integral epoxy coated cast iron roof mounting plate with clamping collar, 1/8" NPT drain port		
	<i>Note: Spec 22 11 19-8 - Domestic Water Piping Specialties;</i>		
CO (Exposed Metal)	CO-460		
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		
	CO-460,2	\$180.00	1
	Watts - 2"Ø (51 mm)		
	CO-460,3	\$224.00	1
	Watts - 3"Ø (76 mm)		
	CO-460,4	\$348.00	1
	Watts - 4"Ø (102 mm)		
	<i>Note: Spec 22 13 19-2 - Sanitary Waste Piping Specialties; Quoting as suggestion.</i>		

FCO (Floor - round)	CO-200-R-6 Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top, vandal proof		
	CO-200-R-6,2 Watts - 2"Ø (51 mm)	\$569.00	1
	CO-200-R-6,3 Watts - 3"Ø (76 mm)	\$597.00	1
	CO-200-R-6,4 Watts - 4"Ø (102 mm)	\$772.00	1
Note: Spec 22 13 19-2 - Sanitary Waste Piping Specialties CARPET MARKER (-RC) = \$61.00 LIST ADDER NB HEAVY DUTY (-RX) = \$122.00 LIST ADDER TILE RECESS (-T) = NO ADDITIONAL TERRAZZO RECESS (-U) = \$279.00 LIST ADDER			
FCO (Floor - square)	CO-200-S-6 Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" x 5" (127 mm x 127 mm) square, nickel bronze top, vandal proof		
	CO-200-S-6,2 Watts - 2"Ø (51 mm)	\$569.00	1
	CO-200-S-6,3 Watts - 3"Ø (76 mm)	\$597.00	1
	CO-200-S-6,4 Watts - 4"Ø (102 mm)	\$772.00	1
Note: Spec 22 13 19-2 - Sanitary Waste Piping Specialties NB HEAVY DUTY (-SX) = \$122.00 LIST ADDER TILE RECESS (-TS) = NO ADDITIONAL TERRAZZO RECESS (-US) = \$279.00 LIST ADDER			
ECO (Equipment room)	CO-270-6 Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 6-9/16" (167 mm) round, heavy duty, ductile iron top, vandal proof		
	CO-270-6,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$433.00	1
Note: Spec 22 13 19-2 - Sanitary Waste Piping Specialties			
WCO (Wall)	CO-380-RD Watts - cast iron body counter sunk, brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-380-RD,2 Watts - 2"Ø (51 mm)	\$183.00	1
	CO-380-RD,3 Watts - 3"Ø (76 mm)	\$226.00	1
	CO-380-RD,4 Watts - 4"Ø (102 mm)	\$271.00	1
	CO-380-RD,6 Watts - 6"Ø (152 mm)	\$574.00	1
Note: Spec 22 13 19-3 - Sanitary Waste Piping Specialties & Spec 22 14 23-3 - Storm Drainage Piping Specialties			
CO (Plug)	CO-590 Watts - Round, threaded brass cleanout plug with countersunk head		
	CO-590,1.5 Watts - 1-1/2"Ø (39 mm)	\$36.00	1
	CO-590,2 Watts - 2"Ø (51 mm)	\$43.00	1

	CO-590,3 Watts - 3"Ø (76 mm)	\$76.00	1
	CO-590,4 Watts - 4"Ø (102 mm)	\$132.00	1
	CO-590,5 Watts - 5"Ø (126 mm)	\$205.00	1
	CO-590,6 Watts - 6"Ø (152 mm)	\$276.00	1
Note: Spec 22 13 19-3 - Sanitary Waste Piping Specialties			
YCO (Yard)	CO-200X-RX-4-C Watts - 7" (178 mm) diameter, cast iron body inside caulk outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top, vandal proof, membrane clamp		
	CO-200X-RX-4-C,2 Watts - 2"Ø (51 mm)	\$416.00	1
	CO-200X-RX-4-C,3 Watts - 3"Ø (76 mm)	\$469.00	1
	CO-200X-RX-4-C,4 Watts - 4"Ø (102 mm)	\$555.00	1
Note: Spec 22 13 19-3 - Sanitary Waste Piping Specialties; Quoting as suggestion Note: For light to medium duty			
YCO (Yard)	CO-300-MF Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top	\$1,099.00	1
	CO-380 Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		
	CO-380,2 Watts - 2"Ø (51 mm)	\$76.00	1
	CO-380,3 Watts - 3"Ø (76 mm)	\$117.00	1
	CO-380,4 Watts - 4"Ø (102 mm)	\$162.00	1
	CO-380,6 Watts - 6"Ø (152 mm)	\$332.00	1
Note: Spec 22 13 19-3 - Sanitary Waste Piping Specialties; Quoting as suggestion			
FD-A (Cast iron floor) / HB	FD-100-A5 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer		
	FD-100-A5,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$380.00	1
	FD-100-A5,6 Watts - 6"Ø (152 mm)	\$475.00	1
Note: Spec 22 13 19-3 - Sanitary Waste Piping Specialties & Spec 22 13 19-6 - Sanitary Waste Piping Specialties; Quoting as suggestion			
FD-B (Mechanical room)	FD-320-Y-5-6 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 8" (203 mm) diameter, ductile iron, heavy duty, round grate, sediment bucket, vandal proof		
	FD-320-Y-5-6,2,3,4 Watts - 2" (51mm), 3" (76mm), 4" (102mm)	\$626.00	1

	FD-320-Y-5-6,6		\$721.00	1
	Watts - 6"(152 mm)			
Note: Spec 22 13 19-3 - Sanitary Waste Piping Specialties. Does not come with Hinged cover, please be advised.				
FD-C (Finished Areas - round)	FD-100-A5-5-6-7	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, adjustable round strainer, sediment bucket, vandal proof, trap primer tapping		
	FD-100-A5-5-6-7,2,3,4		\$508.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
	FD-100-A5-5-6-7,6		\$603.00	1
	Watts - 6"Ø (152 mm)			
Note: Spec 22 13 19-4 - Sanitary Waste Piping Specialties				
FD-D (Kitchen Receptor)	FS-740-175	Watts - cast iron body, 8-1/4" (209 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, porcelain enamel coated cast iron grate, 3/4 grate		
	FS-740-175,2,3,4		\$1,760.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
Note: Spec 22 13 19-4 - Sanitary Waste Piping Specialties				
FD-E (Funnel Drain)	FD-200-DD-50	Watts - 7" (178 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter opening, cast iron hub funnel		
	FD-200-DD-50,2,3,4		\$308.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
Note: Spec 22 13 19-4 - Sanitary Waste Piping Specialties; Note: Trap seal provided by others.				
FD-F (Kitchen Receptor Dishwasher)	FS-850-175	Watts - cast iron body, 12" (305 mm) deep, no-hub outlet, aluminum dome bottom strainer, 13" x 13" (330 mm x 330 mm) square, porcelain enamel coated cast iron grate, 3/4 grate		
	FS-850-175,4,6		\$3,704.00	1
	Watts - 4"Ø (102 mm), 6"Ø (152 mm) outlet size			
Note: Spec 22 13 19-4 - Sanitary Waste Piping Specialties				
Hub drain	FD-100-DD-50	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter opening, cast iron hub funnel		
	FD-100-DD-50,2,3,4		\$357.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
	FD-100-DD-50,6		\$452.00	1
	Watts - 6"Ø (152 mm)			
Note: Spec 22 13 19-6 - Sanitary Waste Piping Specialties				
Vent Cap	RD-680-VC	Watts - cast iron, vandal proof cover		
	RD-680-VC,2,3,4		\$372.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
	RD-680-VC,6		\$530.00	1
	Watts - 6"Ø (152 mm)			
	RD-680-VC,8		\$607.00	1
	Watts - 8"Ø (203 mm)			
Note: Spec 22 13 19-6 - Sanitary Waste Piping Specialties				

TD	P-SP	\$482.00	1
Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) no-hub bottom outlet, pre-sloped trench, pre-sloped trench, 6" (152 mm) wide, including frame connectors, grate lockdowns and construction covers, UV stabilized glass-filled polypropylene frame, framed anchored grate, stainless steel perforated, Class A			
Note: Spec 22 13 19-7 - Sanitary Waste Piping Specialties Note; Quoting as true alternate. Price is per foot.			
MRD	RD-300-B-D-GSS-K		
Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, sump receiver, underdeck clamp, stainless steel ballast guard			
	RD-300-B-D-GSS-K,2,3,4	\$1,620.00	1
Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
	RD-300-B-D-GSS-K,5,6	\$1,860.00	1
Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size			
	RD-300-B-D-GSS-K,8,10	\$2,099.00	1
Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size			
Note: Spec 22 14 23-1 - Storm Drainage Piping Specialties			
DSB	RD-970	\$620.00	1
Watts - epoxy coated, 4" x 3" x 18", cast iron, countersunk securing strap, 4" no hub pipe connection			
Note: Spec 22 14 23-2 - Storm Drainage Piping Specialties; Note: Outlet size is 3".			
DSN	RD-940		
Watts - cast nickel bronze, anchor flange and pre-drilled counter-sunk mounting holes			
	RD-940,2,3,4	\$856.00	1
Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			
	RD-940,5,6	\$1,534.00	1
Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size			
	RD-940,8	\$2,077.00	1
Watts - 8"Ø (203 mm)			
	RD-940,10	\$2,738.00	1
Watts - 10"Ø (254 mm)			
	RD-940,12	\$3,390.00	1
Watts - 12"Ø (305 mm)			

Note: Spec 22 14 23-2 - Storm Drainage Piping Specialties;

NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

NOTE: Watts Drainage does not meet PA.DGS please be advised

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.