

Quotation: Address: 202 Commerce Blvd, Lawrence, Pennsylvania, Phone: (724) 745-5300 15055 United States

Q-233-S

Contractor Holder To:

202 Commerce Blvd., Lawrence, Pennsylvania

Attn.: N/A

Phone: 724-745-5300 **Bid Date:** 2018-05-01 **Expiry Date:** 2018-05-31 **Creator:** Drew Pomrenke,

dpomrenke@jboconnor.com

Sales Rep.: Casey Devlin , cdevlin@jboconnor.com

Shipping Address: , Bethel Park, Pennsylvania, United

States

Job Name: Bethel Park Facility Imp

Architect: EPM Architecture

Comments:

Section Brand: Powers

Label	Product No.	List Price	Qty.
	Description		
TMV	LFMM431AEMS00	\$2,068.00	1
	Powers - HydroGuard Master Tempering Valves Supply Fixture, Bottom Inlets/Top Outlet - Exposed, 42gpm, Rough Bronze, Bottom/Top, $90^{\circ}F - 160^{\circ}F$ ($32^{\circ}C - 71^{\circ}C$)		
Note: P-6.	Water Heater Piping Detail		
TMV PoU	LFE480-10	\$230.00	1

Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough

Bronze Finish

Note: P-7: Plumbing Fixtures K

Section Brand: Watts Regulators

Label	Product No.	List Price	Qty.
	Description		
HB-1	SC8-4	\$65.75	1
	Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)		
Note: P-	1: Fixture Connection Schedule		
RPZ	LF009M2-QT: 1	\$644.00	1
	Watts - Lead Free cast copper silicon alloy body for 1/4" to 2" and fused epoxy coated cast iron body for 2-1/2" and 3", replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules resilient seated isolation valves, resilient seated screw driver slotted test cocks, quarter turn ball-valves, 1"Ø (25 mm) pipe connection (0391004)		
	909-AGC	\$83.75	1
	Watts - 909-AGC Air Gap (0881376)		
	LF777SI: 1	\$79.75	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1"Ø (25 mm) valve (0379113)		
Note: P-	l: Fixture Connection Schedule; Quoting based on Detail DWG.		

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
WHA	SS Series		
Bellows	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$434.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$884.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,321.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$3,313.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$3,740.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$4,596.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: P-1:	Water Hammer Arrestor; Quoting Bellows Option		
WHA	LF15M2-DR Series		
Piston	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$138.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$265.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$418.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$883.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,099.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,308.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: P-1	Water Hammer Arrestor; Quoting Piston Option		
U-1 /U-2	CA-321	\$663.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
Note: P-1	Fixture Connection Schedule		

L-1 /L-2 **TCA-411 Series**

Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.

	TCA-411	\$782.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411-D	\$1,114.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
Note: P-	1: Fixture Connection Schedule		
DSB-1	RD-980	\$989.00	1
	Watts - epoxy coated, $5" \times 4" \times 24"$, cast iron, countersunk securing strap, $4"$ no hub pipe connection		
Note: P-	6: Downspout Boot Detail		
FD	FD-100-A5		
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer		
	FD-100-A5,2,3,4	\$380.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-A5,6	\$475.00	1
	Watts - 6"Ø (152 mm)		
Note: P-	6: Floor Drain Detail		
TP	LFTP300-DR Series		
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	LFTP300T	\$274.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	LFTP300S	\$274.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	LFTP300-DU-DR	\$149.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
Note: P-	6: Floor Drain Trap Primer Detail		
TD-1	D-DI	\$432.00	1
	Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) no-hub bottom outlet(s), pre-sloped trench, 6" (152 mm) wide, including frame connectors, grate lockdowns and construction covers, ductile iron frame, framed anchored grate, ductile iron, Class F		
Note: P-	6: Trench Detail		
FCO	CO-200X-R		
	Watts - 7" (178 mm) diameter, cast iron body inside caulk outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200X-R,2	\$494.00	1
	Watts - 2"Ø (51 mm)		
	CO-200X-R,3	\$522.00	1
	Watts - 3"Ø (76 mm)		
	CO-200X-R,4	\$696.00	1
	Watts - 4"Ø (102 mm)		

Note: P-6: Floor Cleanout Detail;

 $CARPET\ CLAMPING\ FLANGE\ (-CF) = \$225.00\ LIST\ ADDER$

 $CARPET MARKER (-RC) = \$61.00 \ LIST ADDER$ $NB \ HEAVY DUTY (-RX) = \$122.00 \ LIST ADDER$

TILE RECESS (-T) = NO ADDITIONAL

 $TERRAZZO\ RECESS\ (-U) = \$279.00\ LIST\ ADDER$

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Watts Drainage does not meet PA.DGS please be advised

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.