



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-272-S

To:	Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241	Bid Date:	2018-06-01
Attn.:	N/A	Expiry Date:	2018-07-01
Phone:	724-745-5300	Creator:	Drew Pomrenke , dpomrenke@jboconnor.com
		Sales Rep.:	Casey Devlin , cdevlin@jboconnor.com
		Shipping Address:	, Pittsburgh, Pennsylvania, United States

Job Name: Carlow University St Joseph Reno REBID

Engineer: Loftus Engineering **Architect:** MacLachlan Cornelius & Filoni Architects

Comments:

Section Brand: Sloan

Label	Product No. Description	List Price	Qty.
WC-1 /WC-2	ST-2459 Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud (2102459)	\$127.50	1
	Sloan 8111 Sloan - Battery powered, sensor activated, 1-1/2" top spud, exposed closet flushometer. Requires no AC hookups, uses four AA batteries. 1.6 GPF (3790011)	\$547.50	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			
UR-1 /UR-2	SU-1009-A Sloan - Universal Vireous china, 3/4" top spud. 0.125, 0.25 and 0.5 GPF includes dome strainer. (1101009)	\$262.30	1
	Sloan 8186-0.125 Sloan - Battery powered, sensor activated, 3/4" top spud, exposed urinal flushometer. Courtesy flush override button. Requires no AC hookups, uses four AA batteries. Override button 0.125 GPF (3790073)	\$547.50	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			
L-1	SS-3001 Sloan - Standard undermount lavatory, 19-1/2" x 17-1/2" outside, 17" x 14" inside dimensions (3873001)	\$73.55	1
	EFX-200.000.0000 Sloan - Sensor Handwashing Faucet with battery backup, double-infrared sensor activated for pre-tempered or hot and cold water operation. All serviceable components above deck for easy installation and maintenance.(3324031)	\$751.85	1
	EL-154 Sloan - 50 VA Transformer (0345154PK)	\$45.20	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			
L-2	SS-3003 Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$83.40	1
	EFX250.000.0000 Sloan - Basys battery powered, sensor activated, electronic, chrome plated die cast body, hand washing faucet for pre-tempered or hot and cold water operations. 0.5 GPM, (3324005)	\$714.25	1
	EL-154 Sloan - 50 VA Transformer (0345154PK)	\$45.20	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			

Section Brand: Elkay

Label	Product No. Description	List Price	Qty.
S-1	ELUHAD191655PD Elkay - 18 Gauge Stainless Steel 21.5' x 18.5' x 5.375' Single Bowl Undermount Kitchen Sink Kit	\$677.00	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			
S-2	ELUHAD311855PD Elkay - 18 Gauge Stainless Steel 30.75' x 18.5' x 5.375' Double Bowl Undermount Kitchen Sink Kit	\$1,161.00	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			
EWC-1	LZSTLG8WSLC Elkay - (CLR ONLY) VERS LZSTLG8WSLC	\$1,644.00	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			
EWC-2	LZS8WSLP Elkay - BFS FILTRD 8GPH LT GRY	\$1,790.00	1
<i>Note: P0.01 - Plumbing Fixture Schedule</i>			

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
SH-1 /SH-2	P902HM10LYW Powers - Biltmore Series 900 Pressure Balancing Valves	\$931.00	1
<i>Note: P0.01 - Plumbing Fixture Schedule;</i>			
EEW-1	ES150-11 Powers - ES150 EMERGENCY TEMPER	\$913.00	1
<i>Note: P0.01 - Plumbing Fixture Schedule;</i>			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
WMSB-1	2-M2DWB Watts - brass body, 1/2" solder or compression connection, single lever, 3/4" hose connection outlets, 150 psi maximum pressure, 180° F maximum temperature, molded plastic enclosure with top and side knockouts, drain knock out to accommodate waste drain pipe (0006644 & 0006625)	\$161.50	1
<i>Note: P0.01 - Plumbing Fixture Schedule;</i>			
ET-1	PLT-12 Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 4.5 gallons (0067371)	\$104.50	1
<i>Note: P0.01 - Plumbing Fixture Schedule;</i>			
Relief Valve	LFN36M1 : 1/2 Watts - Lead Free Vacuum Relief Valve, 1/2"(15mm)	\$63.25	1
	LFN36M1 : 3/4 Watts - Lead Free brass body construction, Vacuum Relief Valve 3/4"(20mm) (0556031)	\$76.75	1
<i>Note: P5.01 - Water Heating Piping Detail.</i>			
HB	SC8-3 Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, no kink faucet, 1/2" copper sweat connection with vacuum breaker (0611350)	\$65.75	1

SC8-4

\$65.75 1

Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)

Note: Spec 22 11 19 - 5

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
WC-1 /WC-2	ISCA-101-L/R Watts - single, horizontal, cast iron fitting, left/right side outlet	\$1,254.00	1
	ISCA-101-D Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support	\$2,345.00	1
	ISCA-121 Watts - single, vertical, cast iron fitting	\$1,423.00	1
	ISCA-121-D Watts - double, vertical, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts	\$2,514.00	1
	ISCA-131-L/R Watts - single, vertical, cast iron fitting, left/right side outlet	\$1,664.00	1
	ISCA-131-D Watts - double, vertical, epoxy coated, cast iron fitting, 4" no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support	\$2,750.00	1

Note: P0.01 - Plumbing Fixture Schedule

UR-1 /UR-2	CA-321 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$663.00	1
------------	--	----------	---

Note: P0.01 - Plumbing Fixture Schedule

L-2	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$782.00	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,114.00	1

Note: P0.01 - Plumbing Fixture Schedule

SH-1 /SH-2	FD-1100-A5 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, stainless steel, round strainer		
------------	---	--	--

	FD-1100-A5,2,3,4	\$475.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-1100-A5,6	\$570.00	1
	Watts - 6"Ø (152 mm)		
Note: P0.01 - Plumbing Fixture Schedule; Quoting Stainless Steel Drain in-lieu of Chrome plated.			
EWC-1	CA-431-1	\$960.00	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
Note: P0.01 - Plumbing Fixture Schedule			
EWC-2	CA-421	\$594.00	1
	Watts - floor mounted plate type carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
Note: P0.01 - Plumbing Fixture Schedule			
FCO-1	CO-204-R-6	\$772.00	1
	Watts - epoxy coated, cast iron body, 5" (127 mm) round adjustable gasketed nickel bronze top, removable, gas tight, gasketed, brass plug, 4" (102 mm), no hub outlet, vandal proof		
Note: P0.01 - Floor Drain / Cleanout Schedule			
FCO-2	CO-203-R-6	\$597.00	1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top, vandal proof; 3"Ø (76 mm)		
Note: P0.01 - Floor Drain / Cleanout Schedule			
WCO-1	CO-594-RD	\$231.00	1
	Watts - threaded brass cleanout plug with countersunk head, stainless steel access cover and vandal proof stainless steel screw, 4"Ø (102 mm) outlet size		
Note: P0.01 - Floor Drain / Cleanout Schedule			
WCO-2	CO-592-RD	\$141.00	1
	Watts - threaded brass cleanout plug with countersunk head, stainless steel access cover and vandal proof stainless steel screw, 2"Ø (51 mm) outlet size		
Note: P0.01 - Floor Drain / Cleanout Schedule			
FD-1	FD-103-A6-7	\$465.00	1
	Watts - epoxy coated 8-1/8" (206 mm) diameter cast iron body reversible flashing clamp with primary and secondary weepholes no-hub outlet, 6" (152 mm) diameter, nickel bronze, adjustable round strainer, 3" (76 mm), Trap primer tapping		
Note: P0.01 - Floor Drain / Cleanout Schedule			
WHA	SS Series		
Bellows	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$434.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$884.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,321.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$3,313.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$3,740.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$4,596.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		

Note: P0.01 - Water Hammer Arrestor Schedule

TP	LFTP300-DR Series		
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	LFTP300T	\$274.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	LFTP300S	\$274.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	LFTP300-DU-DR	\$149.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
Note: P5.01 - Trap Primer Detail.			
WH-1	HY-725		
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door		
	HY-725,-6,-8	\$1,222.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	HY-725,-10,-12,-14	\$1,335.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-725,-16,-18	\$1,446.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
Note: Spec 22 11 19 - 5			
WH-2	HY-700		
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze, dual-temp, all bronze head, wall mount, concealed, polished bronze hydrant face, integral vacuum breaker, nickel bronze box and door, galvanized casing, 8-1/2" x 6-1/2" (165 mm)		
	HY-700,-6,-8	\$3,057.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	HY-700,-10,-12,-14	\$3,235.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-700,-16,-18	\$3,417.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
Note: Spec 22 11 19 - 5			
WHA Piston	LF15M2-DR Series		
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$138.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$265.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$418.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$883.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,099.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,308.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		

Note: Spec 22 11 19 - 6

ECO	CO-460		
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		
	CO-460,2	\$180.00	1
	Watts - 2"Ø (51 mm)		
	CO-460,3	\$224.00	1
	Watts - 3"Ø (76 mm)		
	CO-460,4	\$348.00	1
	Watts - 4"Ø (102 mm)		

Note: Spec 22 13 19 - 2

Vent Cap	RD-680-VC		
	Watts - cast iron, vandal proof cover		
	RD-680-VC,2,3,4	\$372.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-680-VC,6	\$530.00	1
	Watts - 6"Ø (152 mm)		
	RD-680-VC,8	\$607.00	1
	Watts - 8"Ø (203 mm)		

Note: Spec 22 13 19 - 3

NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.
Pricing good for 30 days.
Pricing subject to change if Mfr pricing changes.
Watts Drainage does not meet PA.DGS please be advised.

Terms

Above prices are net.
All taxes are extra.
Partial or expedited shipments, at customer request, may result in additional freight charges.
Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.
Please ensure that all quoted product meets your projects specifications.
Our company will only be responsible for products shown on the attached quotation.