



**Address:** 202 Commerce Blvd, Lawrence , Pennsylvania ,  
15055 United States

**Phone:** (724) 745-5300

**Quotation:**  
**Q-307-S**

<b>To:</b>	<b>Contractor Holder</b> 202 Commerce Blvd., Lawrence, Pennsylvania 15241	<b>Bid Date:</b>	2018-06-29
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2018-07-29
<b>Phone:</b>	724-745-5300	<b>Creator:</b>	Drew Pomrenke , dpomrenke@jboconnor.com
		<b>Sales Rep.:</b>	Casey Devlin , cdevlin@jboconnor.com
		<b>Shipping Address:</b>	, Johnstown, Pennsylvania, United States

**Job Name: Conemaugh Health System, East Hills Medical Oncology Add**

**Engineer:** CJL Engineering    **Architect:** Inner Design Studio

**Comments:**

**Section Brand: Sloan**

Label	Product No. Description	List Price	Qty.
L-1	<b>SS-3003</b>  Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$83.40	1
<i>Note: Spec 15 400 - 4</i>			
U-1	<b>SU-1006-A</b>  Sloan - Urinal fixture only, 1.0 GPF, 3/4" top spud. Includes Dome strainer (1101006)	\$262.30	1
	<b>ROYAL 186-1 SMO</b>  Sloan - Sensor Exposed Flushometer for Wall Hung Urinals, 11.5" Rough in, SMO, Battery-powered 1 gpf/3.8 Lpf, side mount operator (3912707)	\$494.35	1
<i>Note: Spec 15 400 - 4</i>			
WC1	<b>ST-2009</b>  Sloan - Floor mounted china water closet, 1.28, 1.6/1.1 AND 1.6 GPF, elongated bowl with 1-1/2" IPS top spud. Standard height (2102009).	\$129.95	1
	<b>ROYAL 111 SMO</b>  Sloan - Sensor Exposed Flushometer for Floor Mount or Wall Hung Water Closets, 11.5" Rough in, SMO, Battery-powered 1.6 gpf/6.0 Lpf, side mount operator (3910176)	\$494.35	1
<i>Note: Spec 15 400 - 4,5</i>			
WC2	<b>ST-2029</b>  Sloan - Vitreous china, ADA compliant water closet bowl only, 1.28, 1.6/1.1 AND 1.6 gpf, Floor mounted elongated bowl with 1-1/2" IPS top spud inlet. 1,000 LB load tested (2102029)	\$154.45	1
	<b>ROYAL 111 SMO</b>  Sloan - Sensor Exposed Flushometer for Floor Mount or Wall Hung Water Closets, 11.5" Rough in, SMO, Battery-powered 1.6 gpf/6.0 Lpf, side mount operator (3910176)	\$494.35	1
<i>Note: Spec 15 400 - 4,5</i>			

**Section Brand: Elkay**

Label	Product No. Description	List Price	Qty.
EWC-1	<b>EZSTL8WSLC</b>  Elkay - (CLR ONLY) VERS EZSTL8WSLC	\$1,501.00	1
<i>Note: Spec 15 400 - 2</i>			
S-1	<b>LRAD1918500</b>  Elkay - 18 Gauge Stainless Steel 19' x 18' x 5' Single Bowl Top Mount Kitchen Sink	\$777.00	1

<b>LK99</b>		\$114.00	1
Elkay - DRAIN			
<b>Note:</b> Spec 15 400 - 4			

### Section Brand: Powers

Label	Product No. Description	List Price	Qty.
TMV-1	<b>LFSH1434AEMS000</b> Powers - LFSH1434AEMS000 Sply Fix	\$4,440.00	1
<b>Note:</b> P3.1 - Thermostatic Mixing Valve; Spec 15 111 - 6			
TMV-2	<b>LFLM495-1</b> Powers - 1/2 LFLM495-1	\$252.00	1
<b>Note:</b> P3.1 - Thermostatic Mixing Valve; Spec 15 111 - 7			
TMV-3	<b>ES150AE050</b> Powers - Rough Bronze Valve and Piping Finish, Bottom/Top, T/P Gauge on Inlets	\$1,243.00	1
<b>Note:</b> Spec 15 111 - 7			
TMV-4	<b>ETV400AE050</b> Powers - HydroGuard XP Emergency Tempering Valve with Cold Water Bypass, Rough Bronze, Bottom/Bottom, T/P Gauge on Inlets	\$2,817.00	1
<b>Note:</b> Spec 15 111 - 7			
MB-1	<b>ES150-11</b> Powers - ES150 EMERGENCY TEMPER	\$913.00	1
<b>Note:</b> Spec 15 400 - 4			

### Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
Relief Valve	<b>LFN36M1 : 1/2</b> Watts - Lead Free Vacuum Relief Valve, 1/2"(15mm)	\$63.25	1
	<b>LFN36M1 : 3/4</b> Watts - Lead Free brass body construction, Vacuum Relief Valve 3/4"(20mm) (0556031)	\$76.75	1
<b>Note:</b> P3.1 - Electric Water Heater Piping Schematic			
ET	<b>DETA 12</b> Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 5 gallons (0212027)	\$1,711.00	1
<b>Note:</b> P3.1 - Electric Water Heater Piping Schematic			
DCVA-1	<b>SD2-MF : 1/4</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061651)	\$138.00	1
	<b>SD2-MF : 3/8</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655)	\$146.00	1
	<b>SD3-MF : 1/4</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061653)	\$317.50	1

	<b>SD3-MF : 3/8</b>	\$317.50	1
	Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061657)		
<b>Note:</b> Spec 15 111 - 5			
Dual Check	<b>LF7 : 3/8</b>	\$163.50	1
	Watts - Lead Free cast copper silicon alloy body, silicon disc, 3/8"Ø (10 mm) pipe connection (0792076)		
<b>Note:</b> Spec 15 111 - 5			
HB-1	<b>SC8-2</b>	\$66.00	1
	Watts - Hydrant - cast brass, wall mount, Model 8B tamper-proof vacuum breaker with break-away screw, adjustable packing nut cartridge, no kink faucet, 3/4" (19 mm) male NPT of copper sweat connection with tee handle. (0611250)		
<b>Note:</b> Spec 15 111 - 6			
Drain Box	<b>2-M2DWB</b>	\$161.50	1
	Watts - brass body, 1/2" solder or compression connection, single lever, 3/4" hose connection outlets, 150 psi maximum pressure, 180° F maximum temperature, molded plastic enclosure with top and side knockouts, drain knock out to accommodate waste drain pipe (0006644 & 0006625)		
<b>Note:</b> Spec 15 111 - 6			
VB	<b>LF800M4-FR : 3/4</b>	\$304.50	1
	Watts - acetal bonnet with silicon rubber O-ring seal, Lead Free cast copper silicon alloy body, v-notch guided check assembly full replaceable seats and silicone rubber seat disc, built-in repeatable, automatically re-seating when pressure within the valve is below the set point of freeze relief valve, quarter turn ball valve shut-offs, 3/4"Ø (19 mm) pipe connection (0792017)		
	<b>LF800M4-FR : 1</b>	\$308.00	1
	Watts - acetal bonnet with silicon rubber O-ring seal, Lead Free cast copper silicon alloy body, v-notch guided check assembly full replaceable seats and silicone rubber seat disc, built-in repeatable, automatically re-seating when pressure within the valve is below the set point of freeze relief valve, quarter turn ball valve shut-offs, 1"Ø (25 mm) pipe connection (0792018)		
<b>Note:</b> Spec 15 111 - 6			

## Section Brand: Watts Drainage

**Header:** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

Label	Product No. Description	List Price	Qty.
EWC-1	<b>CA-431-1</b>	\$960.00	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
<b>Note:</b> P3.1 - Plumbing Fixture Schedule			
L-1 /L-3	<b>TCA-411 Series</b>		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>TCA-411</b>	\$782.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		

	<b>TCA-411-D</b>	\$1,114.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<i>Note: P3.1 - Plumbing Fixture Schedule</i>		
U-1	<b>CA-321</b>	\$663.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
	<i>Note: P3.1 - Plumbing Fixture Schedule</i>		
FD-1	<b>FD-104-A5-7</b>	\$380.00	1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer, trap primer connection, 4"Ø (102 mm)		
	<i>Note: P3.1 - Plumbing Fixture Schedule</i>		
FD-2	<b>FD-324-Y</b>	\$401.00	1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 8" (203 mm) diameter, ductile iron grate, 4"Ø (102 mm)		
	<i>Note: P3.1 - Plumbing Fixture Schedule</i>		
RD-1	<b>RD-304-B-D-K</b>	\$1,127.00	1
	Watts - epoxy coated, 16-5/8" (422 mm) diameter, cast iron body, flashing clamp and integral gravel stop, no-hub outlet, self locking, 15-1/4" (387 mm) diameter, 4"(102 mm) outlet size, sump receiver, underdeck clamp, ductile iron dome		
	<b>RD-304-B-D-W-K</b>	\$1,461.00	1
	Watts - epoxy coated, 16-5/8" (422 mm) diameter, cast iron body, flashing clamp and integral gravel stop, no-hub outlet, self locking, 15-1/4" (387 mm) diameter, 4" (102 mm) outlet size, sump receiver, underdeck clamp, 4" Internal Water Dam, ductile iron dome		
	<b>RD-306-D-F-K</b>	\$1,675.00	1
	Watts - epoxy coated, 16-5/8" (422 mm) diameter, cast iron body, flashing clamp and integral gravel stop, no-hub outlet, self locking, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, adjustable extension flange, 6"Ø (152 mm) outlet size		
	<b>RD-306-D-F-W-K</b>	\$2,009.00	1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp and 4" (102 mm) high internal stand pipe, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, adjustable extension flange; 6"Ø (152 mm) outlet size.		
	<i>Note: P3.1 - Plumbing Fixture Schedule</i>		
TP	<b>LFTP300-DR Series</b>		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$274.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$274.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$149.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
	<i>Note: P3.1 - Plumbing Fixture Schedule</i>		
WH-1	<b>HY-725</b>		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door		
	<b>HY-725,-6,-8</b>	\$1,222.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		

<b>HY-725,-10,-12,-14</b>	\$1,335.00	1
Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
<b>HY-725,-16,-18</b>	\$1,446.00	1
Watts - 16" (406 mm), 18" (457 mm) thick		

**Note:** *Spec 15 111 - 6*

**NOTE :** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

**Special Terms:**

All pricing is plus freight unless Mfr freight terms are met.  
Pricing good for 30 days.  
Pricing subject to change if Mfr pricing changes.  
Watts Drainage does not meet PA.DGS please be advised.

**Terms**

Above prices are net.  
All taxes are extra.  
Partial or expedited shipments, at customer request, may result in additional freight charges.  
Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.  
Please ensure that all quoted product meets your projects specifications.  
Our company will only be responsible for products shown on the attached quotation.