



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-285-S

To:	Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241	Bid Date:	2018-06-15
Attn.:	N/A	Expiry Date:	2018-07-15
Phone:	724-745-5300	Creator:	Drew Pomrenke , dpomrenke@jboconnor.com
		Sales Rep.:	Casey Devlin , cdevlin@jboconnor.com
		Shipping Address:	, Youngwood, Pennsylvania, United States

Job Name: Get-Go New Stanton

Engineer: WHS Engineering

Comments:

Section Brand: Sloan

Label	Product No. Description	List Price	Qty.
WC-1/WC-2	ST-2459 Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud (2102459)	\$127.50	1
	SOLIS 8111-1.6 Sloan - Solis Powered, electronic single flush. 1-1/2" top spud, exposed closet flushometer. Requires no AC hookups, uses four AA batteries. 1.6 GPF (3370001)	\$639.10	1
<i>Note: P001 - Plumbing Fixture Schedule; Note: Quoting solar powered flush valve in lieu of hydroelectric.</i>			
UR-1/UR-2	SU-7009-A Sloan - Universal Vitreous china, 3/4" top spud, small urinal. 0.125 to 0.5 GPF (1107009)	\$171.60	1
	SOLIS 8186-0.125 Sloan - Solis Powered, electronic flush valve, 3/4" top spud, exposed urinal flushometer. Courtesy flush override button. Requires no AC hookups, uses four AA batteries. 0.1/8 GPF (3370010)	\$639.10	1
<i>Note: P001 - Plumbing Fixture Schedule; Note: Quoting solar powered flush valve in lieu of hydroelectric.</i>			
L-1/L-2/L-3/L-4	SS-3065 Sloan - 21" x 20" Wall Hung Ledgeback Lavatory-4" CS (3873065)	\$190.55	1
	SS-27 Sloan - White vitreous china Ceramic Shroud 7 3/4" x 10 1/2" x 9 3/4" (197 mm x 267 mm x 248 mm) (387678)	\$189.30	1
	EFX-380.010.0000 Sloan - Turbine powered, sensor activated, electronic, chrome plated die cast body, pedestal hand washing faucet for pre-tempered or hot and cold water operation (3324094)	\$776.85	1
<i>Note: P001 - Plumbing Fixture Schedule</i>			

Section Brand: Elkay

Label	Product No. Description	List Price	Qty.
EWC-1	EZSTL8LC Elkay - VERSATILE BI-LVL 8GPH LT GRY	\$1,538.00	1
<i>Note: P001 - Plumbing Fixture Schedule</i>			

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
L-1/L-2/L-3/L-4	LFE480-10 Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish	\$230.00	1
<i>Note: P001 - Plumbing Fixture Schedule</i>			
Hand Sink	LFLM495-1 Powers - 1/2 LFLM495-1	\$252.00	1
<i>Note: P001 - Plumbing Fixture Schedule</i>			
EEW-1	ES150AEQ500 Powers - ES150 HydroGuard emergency tempering valve with internal cold water bypass, ough bronze valve & pipe finish, SS wall mounted cabinet, gauges on inlets & out.	\$2,268.00	1
<i>Note: P001 - Plumbing Fixture Schedule;</i>			
<i>Note: Cabinet finish not specified, quoting model with stainless steel cabinet.</i>			

Section Brand: Blucher

Label	Product No. Description	List Price	Qty.
TD-1	BWS-228 Blucher - 28"(700mm)	\$880.00	1
	BWS-232 Blucher - 32"(800mm)	\$960.00	1
	BWS-236 Blucher - 36"(900mm)	\$1,040.00	1
	BWS-240 Blucher - 40"(1000mm)	\$1,120.00	1
<i>Note: P001 - Floor Drain/Cleanout Schedule;</i>			
<i>Note: Quoting as alternate.</i>			
<i>Please note trench drain price is per foot.</i>			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
ASSE 1022 Backflow	SD3-MF : 1/4 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061653)	\$317.50	1
	SD3-MF : 3/8 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061657)	\$317.50	1
<i>Note: P001 - Plumbing Equipment Schedule, Note 1</i>			
Strainer	LF777M1-20 : 3/8 Watts - lead free cast copper silicon alloy body, wye-pattern strainer design, lead free copper silicon alloy, solid retainer cap, EPDM gasket, #20 mesh, 304 stainless steel screen, 3/8"Ø (10 mm) valve, threaded connections (0123076)	\$111.00	1

	LF777M1-20 : 1/4	\$111.00	1
	Watts - lead free cast copper silicon alloy body, wye-pattern strainer design, lead free copper silicon alloy, solid retainer cap, EPDM gasket, #20 mesh, 304 stainless steel screen, 1/4"Ø (6 mm) valve, threaded connections (0123075)		
	<i>Note: P001 - Plumbing Equipment Schedule, Note 1</i>		
RPZ	LF909M1-QT : 2	\$2,729.00	1
	Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391012)		
	909-AGF	\$164.00	1
	Watts - 909-AGF Air Gap (0881378)		
	LF777SI : 2	\$239.00	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)		
	<i>Note: P501 - Detail 2;</i>		
	<i>Note: Quoting as per diagram.</i>		
RPZ Alt.	LF009M2-QT : 2	\$1,256.00	1
	Watts - Lead Free cast copper silicon alloy body for 1/4" to 2" and fused epoxy coated cast iron body for 2-1/2" and 3", replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules resilient seated isolation valves, resilient seated screw driver slotted test cocks, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)		
	909-AGF	\$164.00	1
	Watts - 909-AGF Air Gap (0881378)		
	LF777SI : 2	\$239.00	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)		
	<i>Note: P501 - Detail 2;</i>		
	<i>Note: Quoting Alternate Option.</i>		
Expansion Tank	PLT-12	\$104.50	1
	Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 4.5 gallons (0067371)		
	<i>Note: P502 - Detail 1;</i>		
	<i>Note: Quoting as per detail.</i>		

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
WC-1/WC-2	ISCA-101-L/R Watts - single, horizontal, cast iron fitting, left/right side outlet	\$1,254.00	1
	ISCA-101-D Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support	\$2,345.00	1
	ISCA-121 Watts - single, vertical, cast iron fitting	\$1,423.00	1

	ISCA-121-D	\$2,514.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts		
	ISCA-131-L/R	\$1,664.00	1
	Watts - single, vertical, cast iron fitting, left/right side outlet		
	ISCA-131-D	\$2,750.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support		
	Note: P001 - Plumbing Fixture Schedule		
UR-1/UR-2	CA-321	\$663.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
	Note: P001 - Plumbing Fixture Schedule		
L-1/L-2/L-3/L-4	TCA-411-CA-481	\$946.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. W/ wall mounted, steel support, plated hardware.		
	Note: P001 - Plumbing Fixture Schedule		
EWC-1	CA-431-1	\$960.00	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
	Note: P001 - Plumbing Fixture Schedule		
NFWH-1	HY-420		
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, seat casting and internal working parts, wall mount, bronze wall casing, chrome plated face, integral vacuum breaker		
	HY-420,-4,-6,-8	\$683.00	1
	Watts - 4" (102 mm), 6" (152 mm), 8" (203 mm) thick		
	HY-420,-10,-12,-14	\$795.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-420,-16	\$906.00	1
	Watts - 16" (406 mm)		
	Note: P001 - Plumbing Fixture Schedule		
NFRH-1	HY-900	\$2,497.00	1
	Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, roof hydrant with and lift handle and lock option, integral epoxy coated cast iron roof mounting plate with clamping collar, 1/8" NPT drain port		
	Note: P001 - Plumbing Fixture Schedule;		
	<i>Note: Quoting as alternate.</i>		
BWW-1	BV-244	\$3,837.00	1
	Watts - cast iron body, epoxy coated steel access housing, no-hub outlet, bronze seat and flapper, 4" (102 mm) pipe size		
	Note: P001 - Plumbing Fixture Schedule		
TP-1	LFTP300-DR Series		
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		

	LFTP300T	\$274.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	LFTP300S	\$274.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	LFTP300-DU-DR	\$149.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
	Note: P001 - Plumbing Fixture Schedule		
FCO-1	CO-204-RX	\$818.00	1
	Watts - 7" (178 mm) diameter, cast iron body, no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, nickel bronze top, 4"Ø (102 mm) outlet size		
	Note: P001 - Floor Drain/Cleanout Schedule		
WCO-1	CO-594-RD	\$231.00	1
	Watts - threaded brass cleanout plug with countersunk head, stainless steel access cover and vandal proof stainless steel screw, 4"Ø (102 mm) outlet size		
	Note: P001 - Floor Drain/Cleanout Schedule;		
	<i>Note: Quoting as per model number</i>		
FD-1	FD-104P-A5	\$380.00	1
	Watts - epoxy coated 8-1/8" (206 mm) diameter cast iron body reversible flashing clamp with primary and secondary weepholes no-hub outlet, 5" (127 mm) diameter, nickel bronze, adjustable round strainer, push-on outlet, 4" (102 mm)		
	Note: P001 - Floor Drain/Cleanout Schedule		
FD-2	FS-744P-5-F6-1	\$2,506.00	1
	Watts - white porcelain enamel coated interior, 14-7/16" (367 mm) square, cast iron, 8-1/4" (209 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" (229 mm) square, loose set, porcelain enamel coated cast iron grate, push-on outlet, sediment bucket, 6" Round Nickel Bronze Funnel 4" (102mm) outlet size		
	Note: P001 - Floor Drain/Cleanout Schedule		
FD-3	FD-304	\$372.00	1
	Watts - 7" (178 mm) diameter cast iron body no-hub outlet, 7" (178 mm) diameter, heel-proof, ductile iron grate, 4"Ø (102 mm)		
	Note: P001 - Floor Drain/Cleanout Schedule		
HD-1	FD-204-DD-50-5-8	\$691.00	1
	Watts - 7" (178 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter opening, cast iron hub funnel, 4" (102 mm), sediment bucket, ball float backwater valve		
	Note: P001 - Floor Drain/Cleanout Schedule & P501 - FK-P-004;		
	<i>Note: Quoting as suggestion.</i>		
RD-1	RD-304-D-F-K	\$1,435.00	1
	Watts - epoxy coated, 16-5/8" (422 mm) diameter, cast iron body, flashing clamp and integral gravel stop, no-hub outlet, self locking, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, adjustable extension flange, 4"Ø (102 mm) outlet size		
	Note: P001 - Floor Drain/Cleanout Schedule		
RD-2	RD-304-D-F-W-K	\$1,769.00	1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp and 4" (102 mm) high internal stand pipe, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, adjustable extension flange; 4" (102 mm) outlet size		
	Note: P001 - Floor Drain/Cleanout Schedule		
Wall Cleanout	CO-460-RD		
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$287.00	1
	Watts - 2"Ø (51 mm)		

	CO-460-RD,3	\$330.00	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$483.00	1
	Watts - 4"Ø (102 mm)		
Note: P501 - FK-P-007;			
<i>Note: Quoting as per detail.</i>			
DSB	RD-970	\$620.00	1
	Watts - epoxy coated, 4" x 3" x 18", cast iron, countersunk securing strap, 4" no hub pipe connection		
	RD-980	\$989.00	1
	Watts - epoxy coated, 5" x 4" x 24", cast iron, countersunk securing strap, 4" no hub pipe connection		
Note: P502 - Detail 3;			
<i>Note: Quoting as per detail.</i>			
RD (spec)	RD-300-D-F-K80		
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, aluminum dome, underdeck clamp, adjustable extension flange		
	RD-300-D-F-K80,2,3,4	\$1,463.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-300-D-F-K80,5,6	\$1,702.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	RD-300-D-F-K80,8,10	\$1,941.00	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
Note: Spec 22 10 06-2			
DSN	RD-940-83		
	Watts - cast nickel bronze, anchor flange and pre-drilled counter-sunk mounting holes, no hub, stainless steel bird screen		
	RD-940-83,3,4	\$1,289.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-940-83,5,6	\$1,968.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	RD-940-83,8	\$2,511.00	1
	Watts - 8"Ø (203 mm)		
Note: Spec 22 10 06-2			
WHA (Bellows Type)	SS Series		
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$434.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$884.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,321.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$3,313.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$3,740.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$4,596.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		

Note: Spec 22 10 06-3

WHA (Piston Type	LF15M2-DR Series Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$138.00	1
	LF15M2-B-DR Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$265.00	1
	LF15M2-C-DR Watts - 33-60, fixture units, 1" (25 mm) connection	\$418.00	1
	LF15M2-D-DR Watts - 61-113 fixture units, 1" (25 mm) connection	\$883.00	1
	LF15M2-E-DR Watts - 114-154 fixture units, 1" (25 mm) connection	\$1,099.00	1
	LF15M2-F-DR Watts - 155-330 fixture units, 1" (25 mm) connection	\$1,308.00	1

Note: Spec 22 10 06 - 3

NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.