



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-428-S

To:	Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241	Bid Date:	2018-09-27
Attn.:	N/A	Expiry Date:	2018-10-27
Phone:	724-745-5300	Creator:	Drew Pomrenke , dpomrenke@jboconnor.com
		Sales Rep.:	Casey Devlin , cdevlin@jboconnor.com
		Shipping Address:	, Pittsburgh, Pennsylvania, United States

Job Name: Larimer Transit Center Garage Pittsburgh, PA

Engineer: Allen & Shariff Engineering **Architect:** Strada Architecture

Comments:

Section Brand: Sloan

Label	Product No. Description	List Price	Qty.
WC-1/WC-2	ST-2459 Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud (2102459)	\$132.60	1
	Royal 111-1.28 Sloan - Exposed Water Closet Flushometer, for floor mounted or wall hung top spud bowls 1.28 GPF (3910168)	\$211.60	1
<i>Note: 22 42 13.13 - 2; Quoting Bowl based on description.</i>			
L-1	SS-3003 Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$86.75	1
<i>Note: 22 42 13.13 - 2; Quoting Lavatory based on description.</i>			

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
MV-1	LFLM495-1 Powers - 1/2 LFLM495-1	\$252.00	1
<i>Note: P0.01 - Electric Water Heater</i>			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
ET-1	PLT-5 Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 2.1 gallons (0067370)	\$73.25	1
<i>Note: P0.01 - Expansion Tank Schedule</i>			
HB-1	SC8-2 Watts - Hydrant - cast brass, wall mount, Model 8B tamper-proof vacuum breaker with break-away screw, adjustable packing nut cartridge, no kink faucet, 3/4" (19 mm) male NPT of copper sweat connection with tee handle. (0611250)	\$66.00	1
<i>Note: P0.01 - Expansion Tank Schedule</i>			
RELIEF VALVE	LFN36M1 : 1/2 Watts - Lead Free Vacuum Relief Valve, 1/2"(15mm)	\$63.25	1

LFN36M1 : 3/4

\$76.75 1

Watts - Lead Free brass body construction, Vacuum Relief Valve 3/4"(20mm) (0556031)

Note: P0.01 - Electric Water Heater

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised.***

Label	Product No. Description	List Price	Qty.
FD-1	FD-910T-5-6-D Watts - 23-1/2" (597 mm) diameter cast iron body no-hub outlet, 12-1/2" (318 mm) diameter, secured ductile iron grate, gasket seal between body and top assembly, Threaded Outlet (2, 3, 4, 6" only), sediment bucket, vandal proof, Underdeck Clamp		1
	FD-910T-5-6-D,2,3,4,5,6 Watts - 2" (51 mm), 3" (76 mm), 4" (102 mm), 5" (127 mm), 6" (152 mm)	\$3,244.00	1

Note: P0.01 - Drain and Specialties Schedule

FD-2	FD-900T-5-6-D Watts - 20-1/2" (521 mm) diameter cast iron body no-hub outlet, 12-1/2" (318 mm) diameter, secured ductile iron grate, gasket seal between body and top assembly, Threaded Outlet (2, 3, 4, 6" only), sediment bucket, vandal proof, Underdeck Clamp		1
	FD-900T-5-6-D,2,3,4,5,6 Watts - 2" (51 mm), 3" (76 mm), 4" (102 mm), 5" (127 mm), 6" (152 mm)	\$2,717.00	1

Note: P0.01 - Drain and Specialties Schedule

FD-3	P-SS Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) no-hub bottom outlet, pre-sloped trench, pre-sloped trench, 6" (152 mm) wide, including frame connectors, grate lockdowns and construction covers, UV stabilized glass-filled polypropylene frame, framed anchored grate, stainless steel slotted, Class A	\$583.00	1
------	--	----------	---

Note: P0.01 - Drain and Specialties Schedule; Quoting based on description.

RD-1	RD-300-L-K Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, vandal proof		1
	RD-300-L-K,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$945.00	1
	RD-300-L-K,5,6 Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size	\$1,221.00	1
	RD-300-L-K,8,10 Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size	\$1,495.00	1
	RD-300-L-W-K Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, vandal proof, 4" Internal Water Dam		1
	RD-300-L-W-K,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$1,329.00	1
	RD-300-L-W-K,5,6 Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size	\$1,604.00	1
	RD-300-L-W-K,8,10 Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size	\$1,880.00	1

Note: P0.01 - Drain and Specialties Schedule; NOTE: The specified roof drain has one (1) deck plate for both drains. Watts Drainage offers separate standard and overflow roof drains with separate deck plates for this product. When installed side-by-side, our offering is equal to the combination roof drain specified.

FPHB-1	HY-725 Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door		1
--------	--	--	---

	HY-725,-6,-8	\$1,406.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	HY-725,-10,-12,-14	\$1,536.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-725,-16,-18	\$1,663.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	HY-725,-20,-22,-24	\$1,700.00	1
	Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick		
Note: Spec 22 11 19 - 5			
WHA	SS Series		1
Bellows	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$500.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$1,017.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,520.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$3,810.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$4,301.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$5,286.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: Spec 22 11 19 - 6; Quoting Bellows Option			
WHA	LF15M2-DR Series		1
Piston	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$159.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$305.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$481.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$1,016.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,264.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,505.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: Spec 22 11 19 - 6; Quoting Piston Option			
ECO	CO-460		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		
	CO-460,2	\$207.00	1
	Watts - 2"Ø (51 mm)		
	CO-460,3	\$258.00	1
	Watts - 3"Ø (76 mm)		

	CO-460,4	\$401.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 13 19 - 2			
WCO	CO-460-RD		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$331.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$380.00	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$556.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 13 19 - 2; Spec 22 14 23 - 2			
FD	FD-100-A5-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer, trap primer connection		
	FD-100-A5-7,2,3,4	\$437.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-A5-7,6	\$546.00	1
	Watts - 6"Ø (152 mm)		
Note: Spec 22 13 19 - 3			
VENT CAP	RD-680-VC		1
	Watts - cast iron, vandal proof cover		
	RD-680-VC,2,3,4	\$428.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-680-VC,6	\$610.00	1
	Watts - 6"Ø (152 mm)		
	RD-680-VC,8	\$699.00	1
	Watts - 8"Ø (203 mm)		
Note: Spec 22 13 19 - 4			
RD-1	RD-100-GSS-D-F-K		1
	Watts - epoxy coated cast iron roof drain with deep sump, wide serrated flashing flange,membrane clamp, stainless steel 6"(152) high ballast guard with 1/2"(13) x 1/2"(13) drainage openings, dome securing ring gravel stop and self-locking cast dome strainer,Underdeck Clamp,Deck Flange/Adj. Extension,Ductile Iron Dome		
	RD-100-GSS-D-F-K,2,3,4	\$2,220.50	1
	Watts - 2" (51 mm), 3" (76 mm), 4" (102 mm)		
	RD-100-GSS-D-F-K,5,6	\$2,495.50	1
	Watts - 5" (127 mm),6"(152 mm)		
Note: Spec 22 14 23 - 1			
FCO	CO-200-R		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200-R,2	\$569.00	1
	Watts - 2"Ø (51 mm)		
	CO-200-R,3	\$601.00	1
	Watts - 3"Ø (76 mm)		

	CO-200-R,4	\$801.00	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 22 14 23 - 2; CARPET CLAMPING FLANGE (-CF) = \$225.00 LIST ADDER CARPET MARKER (-RC) = \$61.00 LIST ADDER NB HEAVY DUTY (-RX) = \$122.00 LIST ADDER TILE RECESS (-T) = NO ADDITIONAL TERRAZZO RECESS (-U) = \$279.00 LIST ADDER		
WC-1/WC-2	ISCA-101-L/R	\$1,443.00	1
	Watts - single, horizontal, cast iron fitting, left/right side outlet		
	ISCA-101-D	\$2,697.00	1
	Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support		
	ISCA-121	\$1,423.00	1
	Watts - single, vertical, cast iron fitting		
	ISCA-121-D	\$2,892.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts		
	ISCA-131-L/R	\$1,914.00	1
	Watts - single, vertical, cast iron fitting, left/right side outlet		
	ISCA-131-D	\$3,163.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support		
	Note: Spec 22 42 13.13 - 1		
L-1	TCA-411 Series		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411	\$900.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411-D	\$1,282.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	Note: Spec 22 42 16.13 - 1		
	NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised.****		

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.
Pricing good for 30 days.
Pricing subject to change if Mfr pricing changes.
Watts Drainage does not meet PA.DGS please be advised.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.