



**Address:** 202 Commerce Blvd, Lawrence , Pennsylvania ,  
15055 United States

**Phone:** (724) 745-5300

**Quotation:**  
**Q-643-S**

**To:** **Contractor Holder**  
202 Commerce Blvd., Lawrence, Pennsylvania  
15241  
**Attn.:** N/A  
**Phone:** 724-745-5300

**Bid Date:** 2019-03-08  
**Expiry Date:** 2019-04-07  
**Creator:** Drew Pomrenke ,  
dpomrenke@jboconnor.com  
**Sales Rep.:** Casey Devlin , cdevlin@jboconnor.com  
**Shipping Address:** 1701 North Main  
Street, Butler, Pennsylvania, United  
States

**Job Name: JIFFY MART BUTLER**

**Comments:**

**Section Brand: Sloan**

Label	Product No. Description	List Price	Qty.
WC-1	<b>ST-2029-A</b> Sloan - ADA Floor Mount Universal, Top Spud (2102029)	\$160.65	1
	<b>Sloan 8111</b> Sloan - Battery powered, sensor activated, 1-1/2" top spud, exposed closet flushometer. Requires no AC hookups, uses four AA batteries. 1.6 GPF (3790011)	\$569.40	1
<i>Note: Spec 15 400 - 11</i>			
WC-2	<b>ST-2009-STG</b> Sloan - Standard Top Spud Floor Mount Water Closet (2172009)	\$160.10	1
	<b>Sloan 8111</b> Sloan - Battery powered, sensor activated, 1-1/2" top spud, exposed closet flushometer. Requires no AC hookups, uses four AA batteries. 1.6 GPF (3790011)	\$569.40	1
<i>Note: Spec 15 400 - 12</i>			
L-1	<b>SS-3003</b> Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$86.75	1
	<b>EBF-650-8</b> Sloan - Automatic Sink Faucets, 0.5 gpm, 4" Centerset install, 8 inch Trim Plate, Polished Chrome, Activated Sensor (3315139)	\$841.45	1
<i>Note: Spec 15 400 - 12</i>			

**Section Brand: Elkay**

Label	Product No. Description	List Price	Qty.
EWC-1	<b>LVRCTL8SC</b> Elkay - T/L BARRIER FREE CHILD VR WF	\$2,218.00	1
<i>Note: Spec 15 400 - 12</i>			
<i>Note: Quoting model LVRCTL8SC in lieu of LVRCTL85C</i>			

## Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
BFP 1 1/2"	<b>LF009M2-QT : 1 1/2</b> Watts - Lead Free cast copper silicon alloy body for 1/4" to 2" and fused epoxy coated cast iron body for 2-1/2" and 3", replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules resilient seated isolation valves, resilient seated screw driver slotted test cocks, quarter turn ball-valves, 1-1/2"Ø (38 mm) pipe connection (0391006)	\$1,304.00	1
	<b>909-AGF</b> Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	<b>LF777SI : 1 1/2</b> Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/2"Ø (38 mm) valve (0379115)	\$213.00	1
<b>Note:</b> P-2 - Domestic Water Service Entry			
PRV	<b>LF223 : 1 1/2</b> Watts - high capacity water pressure reducing valves,1-1/2" (38 mm) connection with lead-free brass body construction,EPDM valve disc,enlarged diaphragm, spring cage and seat orifice for super capacity,reinforced Buna-N diaphragm,adjustable reduced pressure range: 25 to 75psi (172 to 517 kPa),temperature range: 33°F - 160°F (0.5°C - 71°C),maximum working pressure: 300psi (20.7 bar),standard reduced pressure setting: 50psi (345 kPa). (0298568)	\$3,070.00	1
<b>Note:</b> P-2 - Domestic Water Service Entry <i>Note: Quoting as suggestion.</i>			
Expansion Tank	<b>PLT-12</b> Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 4.5 gallons (0067371)	\$129.00	1
<b>Note:</b> Spec 15 400 - 13			

## Section Brand: Watts Drainage

**Header:** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

Label	Product No. Description	List Price	Qty.
L-1	<b>TCA-411 Series</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	<b>TCA-411</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	<b>TCA-411-D</b> Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
<b>Note:</b> Spec 15 400 - 12			
UR-1	<b>CA-321</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$839.00	1
<b>Note:</b> Spec 15 400 - 12			

EWC-1	<b>CA-431-1</b>		\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.			
<b>Note:</b> Spec 15 400 - 12				
Cleanout Finished	<b>CO-204-R</b>		\$881.00	1
	Watts - epoxy coated, cast iron body, 5" (127 mm) round adjustable gasketed nickel bronze top, removable, gas tight, gasketed, brass plug, 4"Ø (102 mm), no hub outlet.			
<b>Note:</b> Spec 15 400 - 14				
Work Areas Cleanout	<b>CO-204-RX-4</b>		\$596.50	1
	Watts - epoxy coated, cast iron body, 5" (127 mm) round adjustable gasketed heavy duty ductile iron top, removable, gas tight, gasketed, brass plug, 4"Ø (102 mm), no hub outlet.			
<b>Note:</b> Spec 15 400 - 14				
Finish Wall Cleanout (tee)	<b>CO-460-RD</b>			1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw			
	<b>CO-460-RD,2</b>		\$364.00	1
	Watts - 2"Ø (51 mm)			
	<b>CO-460-RD,3</b>		\$417.50	1
	Watts - 3"Ø (76 mm)			
	<b>CO-460-RD,4</b>		\$611.50	1
	Watts - 4"Ø (102 mm)			
<b>Note:</b> Spec 15 400 - 14				
<i>Note: Quoting as suggestion, no model specified.</i>				
Finish Wall Cleanout (line)	<b>CO-380-RD</b>			1
	Watts - cast iron body counter sunk, brass plug, round, stainless steel access cover and stainless steel vandal proof screw			
	<b>CO-380-RD,2</b>		\$232.00	1
	Watts - 2"Ø (51 mm)			
	<b>CO-380-RD,3</b>		\$286.00	1
	Watts - 3"Ø (76 mm)			
	<b>CO-380-RD,4</b>		\$343.50	1
	Watts - 4"Ø (102 mm)			
	<b>CO-380-RD,6</b>		\$727.00	1
	Watts - 6"Ø (152 mm)			
<b>Note:</b> Spec 15 400 - 14				
<i>Note: Quoting as suggestion, no model specified.</i>				
Wall Hydrant	<b>HY-420</b>			1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, seat casting and internal working parts, wall mount, bronze wall casing, chrome plated face, integral vacuum breaker			
	<b>HY-420,-4,-6,-8</b>		\$864.50	1
	Watts - 4" (102 mm), 6" (152 mm), 8" (203 mm) thick			
	<b>HY-420,-10,-12,-14</b>		\$1,006.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick			
	<b>HY-420,-16,-18</b>		\$1,146.50	1
	Watts - 16" (406 mm), 18" (457 mm) thick			
<b>Note:</b> Spec 15 400 - 14				
Shock Absorber	<b>SS Series</b>			1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)			

	<b>SS-A</b>	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>SS-B</b>	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>SS-C</b>	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>SS-D</b>	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>SS-E</b>	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>SS-F</b>	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note:</b> Spec 15 400 - 14			
Trap	<b>LFTP300-DR Series</b>		1
Primer	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$270.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		

**Note:** Spec 15 400 - 15

**NOTE :** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

**Special Terms:**

All pricing is plus freight unless Mfr freight terms are met.  
Pricing good for 30 days.  
Pricing subject to change if Mfr pricing changes.

**Terms**

Above prices are net.  
All taxes are extra.  
Partial or expedited shipments, at customer request, may result in additional freight charges.  
Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.  
Please ensure that all quoted product meets your projects specifications.  
Our company will only be responsible for products shown on the attached quotation.