



**Address:** 202 Commerce Blvd, Lawrence , Pennsylvania ,  
15055 United States

**Phone:** (724) 745-5300

**Quotation:**  
**Q-687-S**

<b>To:</b>	<b>Contractor Holder</b> 202 Commerce Blvd., Lawrence, Pennsylvania 15241	<b>Bid Date:</b>	2019-04-05
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2019-05-05
<b>Phone:</b>	724-745-5300	<b>Creator:</b>	Drew Pomrenke , dpomrenke@jboconnor.com
		<b>Sales Rep.:</b>	Casey Devlin , cdevlin@jboconnor.com
		<b>Shipping Address:</b>	1304 Forbes Ave, Pittsburgh, Pennsylvania, United States

**Job Name: A J Palumbo Center Front Additions Pittsburgh, PA**

**Engineer:** Firsching, Marstiller, Rusbarsky and Wolf Engineering, Inc. **Architect:** DRS Architects

**Comments:**

**Section Brand: Sloan**

Label	Product No. Description	List Price	Qty.
F-1/F-2	<b>ST-2459-STG</b> Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud, with Sloan-Tec Hydrophobic antibacterial glaze (2172459)	\$157.55	1
	<b>ROYAL 111-1.6 SFSM HW</b> Sloan - Battery-powered 1.6 gpf/6.0 Lpf, single flush side mount Hardwired (3910287)	\$548.30	1
	<b>EL-451</b> Sloan - Box mount will operate up to 8 flush valves (0345125)	\$103.80	1
<i>Note: P3-2 - Plumbing Fixture and Accessory Schedule</i>			
F-3	<b>SU-1009-STG</b> Sloan - Universal Vireous china, 3/4" top spud. 0.125, 0.25 and 0.5 GPF includes dome strainer. SloanTec Glaze (1171009)	\$297.75	1
	<b>ROYAL 186-0.5 SFSM HW</b> Sloan - 0.5 gpf Hardwired-3912751	\$548.30	1
	<b>EL-451</b> Sloan - Box mount will operate up to 8 flush valves (0345125)	\$103.80	1
<i>Note: P3-2 - Plumbing Fixture and Accessory Schedule</i>			
F-4	<b>SU-1009-STG</b> Sloan - Universal Vireous china, 3/4" top spud. 0.125, 0.25 and 0.5 GPF includes dome strainer. SloanTec Glaze (1171009)	\$297.75	1
	<b>ROYAL 186-0.5</b> Sloan - Exposed 3/4" top spud 0.5 GPF (3912697)	\$211.60	1
<i>Note: P3-2 - Plumbing Fixture and Accessory Schedule</i>			
F-5	<b>SS-3001</b> Sloan - Standard undermount lavatory, 19-1/2" x 17-1/2" outside, 17" x 14" inside dimensions (3873001)	\$76.50	1
(battery option 1)	<b>EAF-150-CP</b> Sloan - Sensor operated electronic hand washing faucet for pre tempered or hot and cold water. Battery operated. (3335000)	\$745.60	1

(hardwired option 2)	<b>EAF-100-LT-CP</b> Sloan - Electronic operated automatic hand washing faucet. Single supply for pre-mixed water only. Less transformer (LT)(3335012)	\$794.80	1
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------	----------	---

<b>EAF-37</b> Sloan - 6 VDC Box mount adapter, will serve up to 10 EAF faucets (0335037)	\$110.10	1
---------------------------------------------------------------------------------------------	----------	---

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule  
Note: Quoting 1.5 GPM in lieu of 0.5 GPM.

**Section Brand: Elkay**

Label	Product No. Description	List Price	Qty.
F-6	<b>ELUHAD161655</b> Elkay - 18 Gauge Stainless Steel 18.5' x 18.5' x 5.375' Single Bowl Undermount Kitchen Sink	\$641.00	1

<b>LKAD18</b> Elkay - FLAT GRID STRAINER W/OFFSET	\$130.00	1
------------------------------------------------------	----------	---

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule

F-7	<b>EZSTL8LC</b> Elkay - VERSATILE BI-LVL 8GPH LT GRY	\$1,615.00	1
-----	---------------------------------------------------------	------------	---

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule

**Section Brand: Pioneer**

Label	Product No. Description	List Price	Qty.
F-6	<b>0072-GSAELS-Q</b> Pioneer - KITCHEN-CONCEALED 8" TWO 4" WRIST HDLS 4-3/32" GOOSENECK SPT 1/4 TURN-PVD PC	\$173.25	1

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule

F-8	<b>0054-ULE-Q</b> Pioneer - SERVICE SINK-7-7/8" TO 8-1/8" LVR HDL RIGID SPT 1/4 TURN-PC	\$193.00	1
-----	--------------------------------------------------------------------------------------------	----------	---

<b>CS-65001</b> Pioneer - ACCESSORY-STAINLESS STEEL MOP HANGER	\$60.50	1
-------------------------------------------------------------------	---------	---

<b>CS-65002</b> Pioneer - ACCESSORY-HOSE BRACKET W/30" LONG HOSE	\$44.60	1
---------------------------------------------------------------------	---------	---

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule  
Note: Quoting accessories as options.

**Section Brand: Powers**

Label	Product No. Description	List Price	Qty.
TMV (MV-1/MV-2)	<b>SLFIS150DVH003L-3L-200</b> Powers - Mixing Valve Assembly	\$73,300.00	1

**Note:** P2-3 - Keyed Plumbing Notes (This sheet) #4 & P3-2 - Master Mixing Valve Schedule & Spec 22 3400 - 3

F-5 (mixing valve)	<b>LFE480-10</b> Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish	\$284.00	1
-----------------------	--------------------------------------------------------------------------------------------------------------------	----------	---

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule  
Note: Quoting without wall mounting bracket.

F-6 (mixing valve)	<b>LFE480-11</b> Powers - 3/8 LFE480-11	\$332.00	1
-----------------------	--------------------------------------------	----------	---

**Note:** P3-2 - Plumbing Fixture and Accessory Schedule  
Note: Quoting without wall mounting bracket.

**Section Brand: Watts Regulators**

Label	Product No. Description	List Price	Qty.
RPZ 4"	<b>LF909-OSY : 4</b> Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, UL/FM outside stem & yoke gate valve, flange connections, 4"Ø (102 mm) pipe connection (0122763)	\$11,934.00	1
	<b>909-AGK</b> Watts - 909-AGK Air Gap (0881385)	\$408.50	1
	<b>77F-DI-FDA-125 : 4</b> Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 4"Ø (102 mm) valve (0825212)	\$1,042.00	1
<i>Note: P2-2 - Keyed Plumbing Notes (This sheet)</i>			
RPZ 4" Alternate	<b>957-OSY : 4</b> Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 4"Ø (102 mm) pipe connection (0111586)	\$5,200.00	1
	<b>957-AG</b> Watts - 957-AG Air Gap (0111764)	\$269.50	1
	<b>77F-DI-FDA-125 : 4</b> Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 4"Ø (102 mm) valve (0825212)	\$1,042.00	1
<i>Note: P2-2 - Keyed Plumbing Notes (This sheet) #19</i>			
Pressure Reducing Valves	<b>2300: 4</b> Watts - Lead Free Direct Operatr Water Pressure Reducing Valve, 30-80psi, 4"(102mm) (0681060)	\$26,658.00	1
<i>Note: P2-2 - Keyed Plumbing Notes (This sheet) #21</i>			
Beverage BFP	<b>SD3-MF : 1/4</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061653)	\$391.50	1
	<b>SD3-MF : 3/8</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061657)	\$391.50	1
<i>Note: Spec 22 1119 - 3</i>			
Carbonated BFP	<b>SD2-MF : 1/4</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061651)	\$170.50	1
	<b>SD2-MF : 3/8</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655)	\$180.50	1

*Note: Spec 22 1119 - 3*

Hose Bibb	<b>SC8-3</b>	\$81.25	1
Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, no kink faucet, 1/2" copper sweat connection with vacuum breaker (0611350)			
	<b>SC8-4</b>	\$81.25	1
Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)			

**Note:** Spec 22 1119 - 4

Note: Quoting as alternate.

## Section Brand: Watts Drainage

**Header:** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

Label	Product No. Description	List Price	Qty.
Floor Sink	<b>FS-780-F-6</b>		1
Watts - 14 gauge type 304 stainless steel receptor body, 6-1/4" (159 mm) deep, no-hub outlet, dome bottom strainer, 10" x 10" (254 mm x 254 mm) square, cast stainless steel, Flange w/ Weepholes, Vandal Proof			
	<b>FS-780-F-6,2,3,4</b>	\$4,911.00	1
Watts - 2" (51mm), 3" (76mm), 4" (102mm) outlet size			
<b>Note:</b> P2-2 - Keyed Plumbing Notes (This sheet) #23			
Note: Quoting without trap primer connection.			
Grease Interceptor	<b>WD-50-A</b>	\$17,104.00	1
Watts - steel, removable grease accumulating cover and baffle assembly, steel cover, hex head perimeter bolts, internal stainless steel flow control plate, deep seal trap with cleanout, flexible draw-off hose, outlet shut-off valve, IPS threaded connections, flow rate of 50 GPM			
<b>Note:</b> P3-1 - Grease Interceptor Sizing Information			
Solids Interceptor	<b>SI-770-800</b>	\$3,570.00	1
Watts - steel body, gasketed, epoxy coated steel skid-proof cover secured with hex head center bolts, removable sediment basket, flow rate of 50 GPM			
<b>Note:</b> P3-1 - Grease Interceptor Sizing Information			
Extension up to 12" = \$3967.00			
Each additional inch = \$279.50			
F-1/F-2	<b>ISCA-101-L/R</b>	\$1,587.50	1
Watts - single, horizontal, cast iron fitting, left/right side outlet			
	<b>ISCA-101-D</b>	\$2,967.00	1
Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support			
	<b>ISCA-121</b>	\$1,801.00	1
Watts - single, vertical, cast iron fitting			
	<b>ISCA-121-D</b>	\$3,182.00	1
Watts - double, vertical, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts			
	<b>ISCA-131-L/R</b>	\$2,105.50	1
Watts - single, vertical, cast iron fitting, left/right side outlet			

	<b>ISCA-131-D</b>	\$3,479.50	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>		
F-3/F-4	<b>CA-321</b>	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>		
F-7	<b>CA-431-1</b>	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>		
F-7 (trap primer)	<b>LFTP300-DR Series</b>		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$270.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule &amp; P3-1 - Multiple Trap Primer Piping Schematic &amp; Spec 22 1119 - 5</b>		
FD-1	<b>FD-103-M5-7</b>	\$643.00	1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) square, nickel bronze, square strainer, trap primer tapping, 3" (76 mm)		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>		
FD-2	<b>FS-710-FC-3-7</b>		1
	Watts - cast iron body, 6-1/4" (159 mm) deep, no-hub outlet, aluminum dome bottom strainer, 7-11/16" (195 mm) square, porcelain enamel coated cast iron grate,Flange w/Weepholes & Flashing Clamp,Stainless Steel,Trap Primer Tapping		
	<b>FS-710-FC-3-7,2,3,4</b>	\$2,725.50	1
	Watts - 2" (51mm),3" (76mm), 4" (102mm) outlet size		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>		
	<i>Note: Quoting cast iron body in lieu of stainless steel.</i>		
	<i>Note: Quoting as alternate.</i>		
RD-1	<b>RD-300-D-F-K80</b>		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, aluminum dome, underdeck clamp, adjustable extension flange		
	<b>RD-300-D-F-K80,2,3,4</b>	\$1,852.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-300-D-F-K80,5,6</b>	\$2,154.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	<b>RD-300-D-F-K80,8,10</b>	\$2,457.00	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
	<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>		
RD-2	<b>RD-300-D-F-W-K80</b>		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp and 4" (102 mm) high internal stand pipe, no-hub outlet, 15-1/4" (387 mm) diameter, aluminum dome, underdeck clamp, adjustable extension flange		

	<b>RD-300-D-F-W-K80,2,3,4</b>	\$2,275.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-300-D-F-W-K80,5,6</b>	\$2,577.50	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	<b>RD-300-D-F-W-K80,8,10</b>	\$2,880.00	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>			
AD-1 (option 1)	<b>RD-200-CP-1-6</b>		1
	Watts - 8-1/8" (206 mm) diameter cast iron body, flashing clamp, no-hub outlet, 8" x 8" (203 mm x 203 mm) square, all nickel bronze top,Vandal Proof Top		
	<b>RD-200-CP-1-6,2,3,4</b>	\$1,397.00	1
	Watts - 2" (51mm),3" (76mm), 4" (102mm),5"(127 mm)		
<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>			
<i>Note: Quoting as alternate, without sediment bucket.</i>			
AD-1 (option 2)	<b>FD-330-Y-1-5-6</b>		1
	Watts - 8-1/8" (206 mm) diameter, cast iron body no-hub outlet, 8" (203 mm) square, nickel bronze grate, sediment bucket,Vandal Proof		
	<b>FD-330-Y-1-5-6,2,3,4</b>	\$1,730.50	1
	Watts - 2" (51mm),3" (76mm), 4" (102mm),5"(127 mm)		
	<b>FD-330-Y-1-5-6,6</b>	\$1,850.50	1
	Watts - 6" (152 mm) outlet size		
<b>Note: P3-2 - Plumbing Fixture and Accessory Schedule</b>			
<i>Note: Quoting as alternate.</i>			
WHA (bellows type)	<b>SS Series</b>		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	<b>SS-A</b>	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>SS-B</b>	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>SS-C</b>	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>SS-D</b>	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>SS-E</b>	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>SS-F</b>	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note: P3-2 - Water Hammer Arrestor Schedule &amp; Spec 22 1119 - 5</b>			
WHA (piston type)	<b>LF15M2-DR Series</b>		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	<b>LF15M2-A-DR</b>	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>LF15M2-B-DR</b>	\$335.50	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>LF15M2-C-DR</b>	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		

	<b>LF15M2-D-DR</b>	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>LF15M2-E-DR</b>	\$1,391.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>LF15M2-F-DR</b>	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note:</b> P3-2 - Water Hammer Arrestor Schedule & Spec 22 1119 - 5			
Exterior Surfaced Cleanout	<b>CO-200P-RX</b>		1
	Watts - 7" (178 mm) diameter, cast iron body push-on outlet, brass plug, 5" (127 mm) round, heavy duty, nickel bronze top		
	<b>CO-200P-RX,2</b>	\$778.05	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200P-RX,3</b>	\$815.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200P-RX,4</b>	\$1,035.50	1
	Watts - 4"Ø (102 mm)		
<b>Note:</b> Spec 22 1319 - 2 & Spec 22 1423 - 2			
Exterior Unsurfaced	<b>CO-300-MF</b>	\$1,391.00	1
	Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top		
	<b>CO-380</b>		1
	Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		
	<b>CO-380,2</b>	\$96.25	1
	Watts - 2"Ø (51 mm)		
	<b>CO-380,3</b>	\$148.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-380,4</b>	\$205.50	1
	Watts - 4"Ø (102 mm)		
	<b>CO-380,6</b>	\$420.50	1
	Watts - 6"Ø (152 mm)		
<b>Note:</b> Spec 22 1319 - 2 & Spec 22 1423 - 2			
Interior Finished Floor Areas	<b>CO-200P-R</b>		1
	Watts - 7" (178 mm) diameter, cast iron body push-on outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	<b>CO-200P-R,2</b>	\$625.50	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200P-R,3</b>	\$661.00	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200P-R,4</b>	\$881.00	1
	Watts - 4"Ø (102 mm)		
<b>Note:</b> Spec 22 1319 - 2 & Spec 22 1423 - 2			
CARPET CLAMPING FLANGE (-CF) = \$285.00 LIST ADDER			
CARPET MARKER (-RC) = \$78.00 LIST ADDER			
NB HEAVY DUTY (-RX) = \$155.00 LIST ADDER			
TILE RECESS (-T) = NO ADDITIONAL			
TERRAZZO RECESS (-U) = \$354.00 LIST ADDER			
Wall Area Cleanout	<b>CO-460-RD</b>		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		

	<b>CO-460-RD,2</b>	\$364.00	1
	Watts - 2"Ø (51 mm)		
	<b>CO-460-RD,3</b>	\$417.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-460-RD,4</b>	\$611.50	1
	Watts - 4"Ø (102 mm)		
<b>Note:</b> Spec 22 1319 - 2 & Spec 22 1423 - 2			
Cleanout tee	<b>CO-460</b>		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		
	<b>CO-460,2</b>	\$228.00	1
	Watts - 2"Ø (51 mm)		
	<b>CO-460,3</b>	\$284.00	1
	Watts - 3"Ø (76 mm)		
	<b>CO-460,4</b>	\$441.00	1
	Watts - 4"Ø (102 mm)		
<b>Note:</b> Spec 22 1319 - 2			
Brass Plug	<b>CO-590</b>		1
	Watts - Round, threaded brass cleanout plug with countersunk head		
	<b>CO-590,1.5</b>	\$45.75	1
	Watts - 1-1/2"Ø (39 mm)		
	<b>CO-590,2</b>	\$54.50	1
	Watts - 2"Ø (51 mm)		
	<b>CO-590,3</b>	\$96.25	1
	Watts - 3"Ø (76 mm)		
	<b>CO-590,4</b>	\$167.50	1
	Watts - 4"Ø (102 mm)		
	<b>CO-590,5</b>	\$260.00	1
	Watts - 5"Ø (126 mm)		
	<b>CO-590,6</b>	\$349.50	1
	Watts - 6"Ø (152 mm)		
<b>Note:</b> Spec 22 1319 - 2 & Spec 22 1423 - 2			
RD-1 (spec)	<b>RD-300-B-D-K</b>		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, sump receiver, underdeck clamp		
	<b>RD-300-B-D-K,2,3,4</b>	\$1,427.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-300-B-D-K,5,6</b>	\$1,729.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	<b>RD-300-B-D-K,8,10</b>	\$2,031.00	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
<b>Note:</b> Spec 22 1423 - 1			
<b>NOTE :</b> ***NOTE: Watts Drainage does not meet PA.DGS please be advised***			

**Special Terms:**

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.



**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.