



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-718-S

To:	Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241	Bid Date:	2019-04-30
Attn.:	N/A	Expiry Date:	2019-05-30
Phone:	724-745-5300	Creator:	Drew Pomrenke , dpomrenke@jboconnor.com
		Sales Rep.:	Casey Devlin , cdevlin@jboconnor.com
		Shipping Address:	777 Casino Drive, Pittsburgh, Pennsylvania, United States

Job Name: The Landing Hotel - Rivers Casino Pittsburgh, PA

Engineer: Karpinski Engineering

Comments:

Section Brand: Sloan

Label	Product No. Description	List Price	Qty.
L-1	SS-3001 Sloan - Standard undermount lavatory, 19-1/2" x 17-1/2" outside, 17" x 14" inside dimensions (3873001)	\$76.50	1
<i>Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'</i> <i>Note: Quoting as alternate.</i>			
L-2	SS-3103 Sloan - Wall hung lavatory with backsplash, single hole centerset. Overflow, 20.75" x 18.25" (3873103)	\$86.75	1
<i>Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'</i>			
L-3/L-4	SS-3021 Sloan - White vitreous china, Undermount rectangular lavatory fixture. Front overflow, 21-5/8" x 15-3/4" x 8-1/4" (3873021)	\$100.90	1
	EAJ-150-CP Sloan - Sensor operated electronic hand washing faucet for pre tempered or hot and cold water. Battery operated. (3335000)	\$745.60	1
<i>Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'</i> <i>Note: Quoting lavatory as alternate.</i>			
WC-2/WC-3	ST-2459 Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud (2102459)	\$132.60	1
(battery option 1)	SLOAN 111 SMO Sloan - Exposed battery powered, side mount sensor operated water closet flushometer. Metal cover, manual override. 1.6 GPF (3780004)	\$496.25	1
(hardwired option 2)	Sloan 111 ES-S Sloan - Optima sensor activated flushometer for exposed water closets. Equipped with 24V AC solenoid operator and Optima sensor EL-1500-L. Courtesy Flush® Override Button, 1 1/2" top spud. (3770000)	\$635.85	1
	EL-154 Sloan - Box mount, up to 10 flush valves can be operated by one transformer (0345154)	\$47.00	1
<i>Note: P0.02.0 - Plumbing Fixture Schedule 'Flushing Fixtures' Remarks</i> <i>Note: Quoting water closet as suggestion, no model specified.</i>			

U-1/U-2	SU-1009-A	\$272.80	1
	Sloan - Universal Vireous china, 3/4" top spud. 0.125, 0.25 and 0.5 GPF includes dome strainer. (1101009)		
	Royal 186-0.5 SFSM	\$503.10	1
	Sloan - 0.5 gpf/1.9 Lpf For Urinals-3912746		

Note: P0.02.0 - Plumbing Fixture Schedule 'Flushing Fixtures' Remarks

Section Brand: Elkay

Label	Product No. Description	List Price	Qty.
S-1	ELUH1616 Elkay - 18 Gauge Stainless Steel 18.5' x 18.5' x 7.875' Single Bowl Undermount Kitchen Sink	\$609.00	1
	LK99 Elkay - DRAIN	\$120.00	1

Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'
Note: Quoting sink as alternate, with larger dimensions.

EWC-1	EDFPBM117K Elkay - 2 LVL FTN, MP20	\$3,253.00	1
-------	--	------------	---

Note: P0.02.0 - Plumbing Fixture Schedule 'Drinking Fixtures'

Section Brand: Pioneer

Label	Product No. Description	List Price	Qty.
L-1/L-2	3MT170 Pioneer - LAV-MOTEGI SINGLE LVR HDL STRAIGHT SPT W/POP-UP-CP	\$218.00	1

Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'
Note: Quoting as alternate, quoting shorter spout length and 1.2 GPM in lieu of 1.5 GPM.

S-1 (option 1)	2MT171H Pioneer - KIT-MOTEGI 2-HOLE SINGLE LVR HDL GOOSENECK SPT W/SIDE SPRAY 3/8" FLEX-CP	\$396.00	1
-------------------	--	----------	---

Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'
Note: Quoting as alternate, quoting with side spray.

S-1 (option 2)	2MT261 Pioneer - KIT-MOTEGI 1 HOLE SINGLE LVR HDL GOOSENECK SPT W/PULL-DOWN SPRAY HEAD 3/8" FLEX-CP	\$416.00	1
-------------------	---	----------	---

Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'
Note: Quoting as alternate, with pull down spray.

MB-1	0047-SLE0 Pioneer - KITCHEN-WALLMOUNT 6-1/2" TO 9-1/2" LVR HDL 6" TUBE SPT-PC	\$125.85	1
------	---	----------	---

Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
SH-1/BT-1	P910HH1000 Powers - Pressure Balancing Valve, 1/2" Copper sweat connection, Low Flow Shower (1.5 gpm), Arm & Flange	\$407.00	1

Note: P0.02.0 - Plumbing Fixture Schedule 'Bathing Fixtures'
Note: Quoting as alternate.

SH-2/SH-3/SH-4	P910H0001W	\$782.00	1
	Powers - All Series 900 Pressure Balancing Mixing Valves, ABS faceplate with color-coded graphics, metal lever handle. CP finish. 1/2" Copper Sweat Connections, 24" Chrome ADA Wall Grab Bar System, in-line Vacuum Breaker		

Note: P0.02.0 - Plumbing Fixture Schedule 'Bathing Fixtures'

Note: Quoting as alternate.

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
ASSE 1070 Mixing Valve	LFUSG-B-M2 Watts - Lead Free brass body construction, copper thermostat with stainless steel springs, integral checks and 40 mesh stainless steel screens, 4-port with cap for three port application, "H" pattern body, ASSE 1070 and cUPC, valve shall control temperature from a low of 1/4gpm, 3/8"Ø (10 mm) male compression (0204143)	\$297.50	1

Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures' Notes

Note: Quoting as alternate.

BFP 2" make-up	LF009M2-QT : 2 Watts - Lead Free cast copper silicon alloy body for 1/4" to 2" and fused epoxy coated cast iron body for 2-1/2" and 3", replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules resilient seated isolation valves, resilient seated screw driver slotted test cocks, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)	\$1,548.00	1
-------------------	--	------------	---

909-AGF Watts - 909-AGF Air Gap (0881378)	\$208.00	1
---	----------	---

LF777SI : 2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
--	----------	---

Note: P5.01.0 - Enlarged Mechanical Room Plan

ASSE 1024 Dual Check Valve	LF7 : 3/8 Watts - Lead Free cast copper silicon alloy body, silicon disc, 3/8"Ø (10 mm) pipe connection (0792076)	\$202.00	1
-------------------------------------	---	----------	---

Note: P5.06.0 - Remarks #2

ASSE 1022 Dual Check Valve	SD3-MF : 1/4 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061653)	\$391.50	1
-------------------------------------	--	----------	---

SD3-MF : 3/8 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061657)	\$391.50	1
---	----------	---

Note: P5.06.0 - Remarks #3

BFP 3"	957-OSY : 3 Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 3"Ø (76 mm) pipe connection (0111585)	\$4,700.00	1
--------	---	------------	---

957-AG Watts - 957-AG Air Gap (0111764)	\$269.50	1
---	----------	---

	77F-DI-FDA-125 : 3	\$680.50	1
	Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 3"Ø (76 mm) valve (0825211)		
	Note: P6.02.0 - Domestic Water Building Entry Diagram		
Pressure Reducing Valve	2300: 4 Watts - Lead Free Direct Operatr Water Pressure Reducing Valve, 30-80psi, 4"(102mm) (0681060)	\$26,658.00	1
	Note: P6.02.0 - Domestic Water Building Entry Diagram <i>Note: Quoting as suggestion as per detail.</i>		
BFP 4" Irrigation	957-OSY : 4 Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 4"Ø (102 mm) pipe connection (0111586)	\$5,200.00	1
	957-AG Watts - 957-AG Air Gap (0111764)	\$269.50	1
	77F-DI-FDA-125 : 4 Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 4"Ø (102 mm) valve (0825212)	\$1,042.00	1
	Note: P6.03.0 - Water Distribution Diagram <i>Note: Quoting as suggestion as per detail.</i>		

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
L-2	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
	Note: P0.02.0 - Plumbing Fixture Schedule 'Basin Fixtures'		
WC-2/WC-3	ISCA-101-L/R Watts - single, horizontal, cast iron fitting, left/right side outlet	\$1,587.50	1
	ISCA-101-D Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support	\$2,967.00	1
	ISCA-121 Watts - single, vertical, cast iron fitting	\$1,801.00	1

	ISCA-121-D		\$3,182.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts			
	ISCA-131-L/R		\$2,105.50	1
	Watts - single, vertical, cast iron fitting, left/right side outlet			
	ISCA-131-D		\$3,479.50	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support			
	Note: P0.02.0 - Plumbing Fixture Schedule 'Flushing Fixtures'			
U-1/U-2	CA-321		\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.			
	Note: P0.02.0 - Plumbing Fixture Schedule 'Flushing Fixtures'			
EWC-1	CA-431-1		\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.			
	Note: P0.02.0 - Plumbing Fixture Schedule 'Drinking Fixtures'			
Outside Cleanout	CO-200-RX-4			1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top			
	CO-200-RX-4,2		\$420.50	1
	Watts - 2"Ø (51 mm)			
	CO-200-RX-4,3		\$487.50	1
	Watts - 3"Ø (76 mm)			
	CO-200-RX-4,4		\$596.50	1
	Watts - 4"Ø (102 mm)			
	Note: P6.01.0 - Outside Cleanout Detail			
	<i>Note: Quoting as alternate.</i>			
Trap Primer	LFTP300-DR Series			1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap			
	LFTP300T		\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect			
	LFTP300S		\$270.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect			
	LFTP300-DU-DR		\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit			
	Note: P6.01.0 - Trap Primer Detail			
	<i>Note: Quoting mechanical type.</i>			
	NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***			

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.