



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-720-S

| | | | |
|---------------|---|--------------------------|--|
| To: | Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241 | Bid Date: | 2019-05-01 |
| Attn.: | N/A | Expiry Date: | 2019-05-31 |
| Phone: | 724-745-5300 | Creator: | Drew Pomrenke , dpomrenke@jboconnor.com |
| | | Sales Rep.: | Casey Devlin , cdevlin@jboconnor.com |
| | | Shipping Address: | 45th Street and Penn Avenue, Pittsburgh, Pennsylvania, United States |

Job Name: UPMC Children's - Nursing Unit 7C Pittsburgh, PA

Engineer: Allen & Shariff Engineering

Comments:

Section Brand: Sloan

| Label | Product No. Description | List Price | Qty. |
|---|--|------------|------|
| WC-12 | ST-2459 Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud (2102459) | \$132.60 | 1 |
| | ROYAL BPW-1150-1.6 Sloan - Bedpan washer water closet flushometer for floor mounted or wall hung top spud bowls. Installation meets ADA requirements. 1 1/2" top spud. 1.6 GPM (3919711) | \$689.40 | 1 |
| <i>Note: P001 - Plumbing Fixture Connection Schedule</i> | | | |
| <i>Note: Quoting as suggestion, complete model not specified.</i> | | | |
| WC-13 | ST-2459 Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud (2102459) | \$132.60 | 1 |
| | Royal 111 ES-S Sloan - Hardwired 1.6 gpf/6.0 Lpf, electronic sensor solenoid operated (3450047) | \$697.65 | 1 |
| | EL-154 Sloan - Box mount, up to 10 flush valves can be operated by one transformer (0345154) | \$47.00 | 1 |
| <i>Note: P001 - Plumbing Fixture Connection Schedule</i> | | | |
| <i>Note: Quoting hardwired as suggestion, complete model not specified.</i> | | | |
| S-2 | SS-3103 Sloan - Wall hung lavatory with backsplash, single hole centerset. Overflow, 20.75" x 18.25" (3873103) | \$86.75 | 1 |
| <i>Note: P001 - Plumbing Fixture Connection Schedule</i> | | | |
| S-13 | SS-3103 Sloan - Wall hung lavatory with backsplash, single hole centerset. Overflow, 20.75" x 18.25" (3873103) | \$86.75 | 1 |
| | ETF-700-H-4-P Sloan - Automatic Sink Faucets, 1.58 gpm, Single Holeinstall, 4 inch Trim Plate, Polished Chrome, Activated Sensor (3365010) | \$922.35 | 1 |
| | ETF-233 Sloan - Plug in type transformer (Up to 2 faucets can be operated) (0365534) | \$33.30 | 1 |

Note: P001 - Plumbing Fixture Connection Schedule
Note: Quoting faucet as alternate.

Section Brand: Pioneer

| Label | Product No. Description | List Price | Qty. |
|----------|---|------------|------|
| S-2/S-11 | 0287-GSAELS-Q Pioneer - BAR/PANTRY-1 HOLE TWO 4" WRIST HDLS 4-3/32" GOOSENECK SPT 1/4 TURN-PVD PC | \$174.60 | 1 |

*Note: P001 - Plumbing Fixture Connection Schedule
Note: Quoting as alternate.*

| | | | |
|------|--|----------|---|
| S-12 | 0072-GSAELS-Q Pioneer - KITCHEN-CONCEALED 8" TWO 4" WRIST HDLS 4-3/32" GOOSENECK SPT 1/4 TURN-PVD PC | \$173.25 | 1 |
|------|--|----------|---|

*Note: P001 - Plumbing Fixture Connection Schedule
Note: Quoting 1.5 GPM.*

Section Brand: Powers

| Label | Product No. Description | List Price | Qty. |
|-------|---|------------|------|
| SH-4 | P910HH102WY Powers - Pressure Balancing Mixing Valve, 1/2" copper sweat connections, Low Flow Shower (1.5gpm), Arm & Flange, 36" Chrome ADA Wall Grab Bar System, Vacuum Breaker,in-Line, Diverter Concealed, 1/2" IPS Metal Handle | \$1,132.00 | 1 |

Note: P001 - Plumbing Fixture Connection Schedule

Section Brand: Watts Regulators

| Label | Product No. Description | List Price | Qty. |
|------------------|---|------------|------|
| ASSE 1070 TMV | LFUSG-B-M2 Watts - Lead Free brass body construction, copper thermostat with stainless steel springs, integral checks and 40 mesh stainless steel screens, 4-port with cap for three port application, "H" pattern body, ASSE 1070 and cUPC, valve shall control temperature from a low of 1/4gpm, 3/8"Ø (10 mm) male compression (0204143) | \$297.50 | 1 |

*Note: P001 - Detail 1 & 2
Note: Quoting as alternate.*

| | | | |
|------------------------|--|----------|---|
| Dual Check Valve | SD2-MF : 1/4 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061651) | \$170.50 | 1 |
|------------------------|--|----------|---|

| | | | |
|--|---|----------|---|
| | SD2-MF : 3/8 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655) | \$180.50 | 1 |
|--|---|----------|---|

Note: P001 - Detail 3

Section Brand: Watts Drainage

Header: *NOTE: Watts Drainage does not meet PA.DGS please be advised*****

| Label | Product No. Description | List Price | Qty. |
|-------------|--|------------|------|
| WC-12/WC-13 | ISCA-101-L/R Watts - single, horizontal, cast iron fitting, left/right side outlet | \$1,587.50 | 1 |

| | | | |
|--|---|------------|---|
| | ISCA-101-D | \$2,967.00 | 1 |
| | Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support | | |
| | ISCA-121 | \$1,801.00 | 1 |
| | Watts - single, vertical, cast iron fitting | | |
| | ISCA-121-D | \$3,182.00 | 1 |
| | Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts | | |
| | ISCA-131-L/R | \$2,105.50 | 1 |
| | Watts - single, vertical, cast iron fitting, left/right side outlet | | |
| | ISCA-131-D | \$3,479.50 | 1 |
| | Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support | | |
| Note: P001 - Plumbing Fixture Connection Schedule | | | |
| S-2 | TCA-411 Series | | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| | TCA-411 | \$989.50 | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| | TCA-411-D | \$1,411.00 | 1 |
| | Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| Note: P001 - Plumbing Fixture Connection Schedule | | | |
| FD-1 | FD-100-A5 | | 1 |
| | Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer | | |
| | FD-100-A5,2,3,4 | \$481.00 | 1 |
| | Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | | |
| | FD-100-A5,6 | \$601.50 | 1 |
| | Watts - 6"Ø (152 mm) | | |
| Note: P001 - Plumbing Fixture Connection Schedule | | | |
| <i>Note: Quoting as suggestion, model specified not found.</i> | | | |
| Water Hammer Arrestor | LF15M2-DR Series | | 1 |
| | Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C) | | |
| | LF15M2-A-DR | \$175.00 | 1 |
| | Watts - 1-11 fixture units, 1/2" (13 mm) connection | | |
| | LF15M2-B-DR | \$335.50 | 1 |
| | Watts - 12-32 fixture units, 3/4" (19 mm) connection | | |
| | LF15M2-C-DR | \$529.50 | 1 |
| | Watts - 33-60, fixture units, 1" (25 mm) connection | | |

| | | | |
|------------------------------|--|------------|---|
| | LF15M2-D-DR | \$1,118.00 | 1 |
| | Watts - 61-113 fixture units, 1" (25 mm) connection | | |
| | LF15M2-E-DR | \$1,391.00 | 1 |
| | Watts - 114-154 fixture units, 1" (25 mm) connection | | |
| | LF15M2-F-DR | \$1,656.00 | 1 |
| | Watts - 155-330 fixture units, 1" (25 mm) connection | | |
| Note: P001 - Detail 3 | | | |
| Trap | LFTP300-DR Series | | 1 |
| Primer | Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap | | |
| | LFTP300T | \$270.00 | 1 |
| | Watts - 1/2", Threaded Inlet and Outlet Connect | | |
| | LFTP300S | \$270.00 | 1 |
| | Watts - 1/2", Soldered Inlet and Outlet Connect | | |
| | LFTP300-DU-DR | \$189.00 | 1 |
| | Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit | | |

Note: P001 - Detail 4

NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.