Address: 202 Commerce Blvd, Lawrence , Pennsylvania , Phone: (724) 745-5300 Quotation: 15055 United States Q-724-S

To: Contractor Holder Bid Date: 2019-05-06

202 Commerce Blvd., Lawrence, Pennsylvania **Expiry Date:** 2019-06-05 15241 **Creator:** Drew Pomrenke ,

N/A dpomrenke@jboconnor.com

Sales Rep.: Casey Devlin , cdevlin@jboconnor.com

Shipping Address: Fifth Avenue Place, 120 Fifth

Avenue, Pittsburgh, Pennsylvania, United

States

Job Name: Highmark FAP 19th Fl Reno Pittsburg,PA

Engineer: Firsching, Marstiller, Rusbarsky and Wolf Engineering, Inc. Architect: Designstream Architects

Comments:

Attn.:

Phone:

Section Brand: Sloan

724-745-5300

Label	Product No. Description	List Price	Qty.
F-1/F-2	G2 OPTIMA PLUS 8111-1.28	\$637.25	1
	Sloan - Sensor Exposed Flushometer for Floor Mount or Wall Hung Water Closets, 11.5" Rough in, Battery-powered 1.28 gpf/4.8 Lpf (3250289)		
Note: P-2	200 - Plumbing Fixture Schedule and Specifications		
F-3/F-4	ECOS 8186-0.125	\$606.95	1
	Sloan - Ecos electronic Battery powered, sensor activated, 3/4" top spud, exposed urinal flushometer. Courtesy flush override button. Requires no AC hookups, uses four AA batteries. Overide button 0.13 GPF (3250325)		

Note: P-200 - Plumbing Fixture Schedule and Specifications

F-5 SS-3001 \$76.50 1
Sloan - Standard undermount lavatory, 19-1/2" x 17-1/2" outside, 17" x 14" inside dimensions (3873001)

SF-2450-4 \$458.50 1

Sloan - Sensor activated, battery operated, 4" trim plate, 0.5 GPM flow spary head, Pedestal hand washing faucet for tempered or hot/cold water operation (3362124)

Note: P-200 - Plumbing Fixture Schedule and Specifications

Note: Quoting lavatory and faucet as alternate.

ELUHAD211555

Section Brand: Elkay

F-6

Label	Product No. Description	List Price	Qty.
F-6	ELUH2115	\$666.00	1
	Elkay - 18 Gauge Stainless Steel 23.5' x 18.25' x 7.5' Single Bowl Undermount Kitchen Sink		
	LK18B	\$78.00	1
	Elkay - DRAIN		
	200 - Plumbing Fixture Schedule and Specifications oting as per model number (7 1/2" depth)		

Elkay - 18 Gauge Stainless Steel 23.5' x 18.25' x 5.375' Single Bowl Undermount Kitchen Sink

\$694.00

LK18B \$78.00 1

Elkay - DRAIN

Note: P-200 - Plumbing Fixture Schedule and Specifications

Note: Quoting as per description (5 1/2" depth)

F-8 **EZS8L** \$922.00 1

Elkay - BARRIER FREE FRONT/SIDE

Note: P-200 - Plumbing Fixture Schedule and Specifications

Section Brand: Pioneer

Label	Product No.	List Price	Qty.
	Description		
F-6	2MT182H	\$292.00	1

Pioneer - KIT-MOTEGI 2-HOLE SINGLE LVR HDL 90 DEGREE SPT W/SIDE SPRAY 3/8" FLEX-CP

Note: P-200 - Plumbing Fixture Schedule and Specifications

Note: Quoting as alternate with side spray separate from main faucet.

Note: Quoting 1.5 GPM in lieu of 1.8 GPM.

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
Dual	SD2-MF: 3/8	\$180.50	1
Check Valve	Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655)		
Note: P-10	00 - Keyed Plumbing Notes #11		
Vacuum	LFN36M1: 3/4	\$97.75	1
Relief Valve	Watts - Lead Free brass body construction, Vacuum Relief Valve 3/4"(20mm) (0556031)		
Note: P-10	01 - 19th Floor Electric Water Heater Piping Schematic		
Expansion	PLT-20	\$254.50	1
Tank	Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 8.5 gallons (0067372)		
	01 - 19th Floor Electric Water Heater Piping Schematic ing 8.5 gallon capacity.		
F-5	LFUSG-B-SC-M2	\$465.50	1
(mixing valve)	Watts - Lead Free brass body construction, copper thermostat with stainless steel springs, integral checks and 40 mesh stainless steel screens, 4-port with cap for three port application, "H" pattern body, ASSE 1070 and cUPC, satin chrome finish, valve shall control temperature from a low of 1/4gpm, 3/8"Ø (10 mm) male compression (0204144)		
Note: P-20	00 - Plumbing Fixture Schedule and Specifications		
F-6	LFUSG-B-M2	\$297.50	1
(mixing valve)	Watts - Lead Free brass body construction, copper thermostat with stainless steel springs, integral checks and 40 mesh stainless steel screens, 4-port with cap for three port application, "H" pattern body, ASSE 1070 and cUPC, valve shall control temperature from a low of 1/4gpm, 3/8"Ø (10 mm) male compression (0204143)		
Note: P-20	00 - Plumbing Fixture Schedule and Specifications		

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
Floor Drain	FD-100-M6-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6 " x 6 " (152 mm x 152 mm) nickel bronze, square strainer, trap primer connection		
	FD-100-M6-7,2,3,4	\$716.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-M6-7,6	\$836.50	1
	Watts - 6"Ø (152 mm)		
	11 - Keyed Plumbing Notes #10 & Spec 22 1319 - 2 seal by others.		
Trap	LFTP300-DR Series		1
Primer	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	LFTP300T	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	LFTP300S	\$270.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect	·	
	LFTP300-DU-DR	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit	Ψ200.00	_
	11 - Keyed Plumbing Notes #11 & P-200 - Trap Primer Piping Schematic ing as alternate.		
F-1/F-2	ISCA-103-D	\$6,328.00	1
	Watts - epoxy coated cast iron fitting, 4 in(102mm) no hub waste and 2 in(51mm) no hub vent connections, epoxy coated cast iron patented compression seal faceplate assembly, epoxy coated cast iron foot supports adjustable for standard and wheelchair height, adjustable ABS nipple with integral test cap and neoprene bowl gasket, stainless steel rods and hardware, and chrome plated cap nuts.		
	ISCA-123	\$3,713.00	1
	Watts - epoxy coated cast iron fitting, 4"(102) no hub waste and 2"(51) no hub vent connections, epoxy coated cast iron patented compression seal faceplate assembly, epoxy coated cast iron foot supports adjustable for standard and wheelchair height, ductile iron rear anchor support, adjustable ABS nipple with integral test cap and neoprene bowl gasket, stainless steel support rods and hardware, and chrome plated cap nuts.		
	ISCA-123-D	\$7,154.00	1
	Watts - epoxy coated cast iron fitting, 4 in(102mm) no hub waste and 2 in(51mm) no hub vent connections, epoxy coated cast iron patent pending compression seal faceplate assembly, epoxy coated cast iron foot supports adjustable for standard and wheelchair height, adjustable ABS nipple with integral test cap and neoprene bowl gasket, plated hardware and chrome cap nuts.		
	ISCA-133-D	\$7,454.00	1
	Watts - epoxy coated cast iron fitting, 4 in(102mm) no hub waste and 2 in(51mm) no hub vent connections, 4 in(102mm) no hub side inlet(s), epoxy coated cast iron patented compression seal faceplate assembly, epoxy coated cast iron foot supports adjustable for standard and wheelchair height, adjustable ABS nipple with integral test cap and neoprene bowl gasket, plated hardware and chrome cap nuts.		
	ISCA-103-L/R	\$3,284.00	1
	Watts - epoxy coated cast iron fitting, 4 in.(102mm) no hub waste and 2 in.(51mm) no hub vent connections, epoxy coated cast iron patented compression seal faceplate assembly, epoxy coated cast iron foot supports adjustable for standard and wheelchair height, ductile iron rear anchor support, adjustable ABS nipple with integral test cap and neoprene bowl gasket, stainless steel support rods and hardware, and chrome plated cap nuts		

	ISCA-133-L/R/2	\$4,017.50	1
	Watts - epoxy coated cast iron fitting, 4"(102) no hub waste and 2"(51) no hub vent connections, 4"(102) no hub side inlet(s), epoxy coated cast iron patented compression seal faceplate assembly, epoxy coated cast iron foot supports adjustable for standard and wheelchair height, ductile iron rear anchor support, adjustable ABS nipple with integral test cap and neoprene bowl gasket, stainless steel support rods and hardware, and chrome plated cap nuts.		
	00 - Plumbing Fixture Schedule and Specifications ted carriers are rated for 750lbs.		
F-3/F-4	CA-321	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	,	
Note: P-2	00 - Plumbing Fixture Schedule and Specifications		
F-7/F-8	CA-421	\$752.00	1
(single level)	Watts - floor mounted plate type carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
Note: P-2	00 - Plumbing Fixture Schedule and Specifications		
WHA	LF15M2-DR Series		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$335.50	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,391.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: Spe	nc 22 1119 - 3		
Interior Cleanout	CO-200P-R		1
Cleariout	Watts - 7" (178 mm) diameter, cast iron body push-on outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200P-R,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200P-R,3	\$661.00	1
	Watts - 3"Ø (76 mm)		
	CO-200P-R,4	\$881.00	1
	Watts - 4"Ø (102 mm)		
CARPET CL CARPET M, NB HEAVY TILE RECES	CC 22 1319 - 2 AMPING FLANGE (-CF) = \$285.00 LIST ADDER ARKER (-RC) = \$78.00 LIST ADDER DUTY (-RX) = \$155.00 LIST ADDER S (-T) = NO ADDITIONAL RECESS (-U) = \$354.00 LIST ADDER		
Interior	CO-460-RD		1
Wall Clenout	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		-

	CO-460-RD,2	\$364.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$417.50	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$611.50	1
	Watts - 4"Ø (102 mm)		
	oc 22 1319 - 2 ting as per description.		
Floor	CO-300-MF	\$1,391.00	1
Cleanout Housing	Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top		
	CO-380		1
	Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		
	CO-380,2	\$96.25	1
	Watts - 2"Ø (51 mm)		
	CO-380,3	\$148.50	1
	Watts - 3"Ø (76 mm)		
	CO-380,4	\$205.50	1
	Watts - 4"Ø (102 mm)		
	CO-380,6	\$420.50	1
	Watts - 6"Ø (152 mm)		
	oc 22 1319 - 2 ting as per model number.		
Cleanout	CO-590		1
plug	Watts - Round, threaded brass cleanout plug with countersunk head		
	CO-590,1.5	\$45.75	1
	Watts - 1-1/2"Ø (39 mm)		
	CO-590,2	\$54.50	1
	Watts - 2"Ø (51 mm)		
	CO-590,3	\$96.25	1
	Watts - 3"Ø (76 mm)		
	CO-590,4	\$167.50	1
	Watts - 4"Ø (102 mm)		
	CO-590,5	\$260.00	1
	Watts - 5"Ø (126 mm)		
	CO-590,6	\$349.50	1
	Watts - 6"Ø (152 mm)		
Note: Spe	oc 22 1319 - 2		

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Note: Quoting as per description.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

 $\label{partial or expedited shipments, at customer request, may result in additional freight charges. \\$

NOTE: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

 $Any \ material \ over \ \& \ above \ that \ what \ is \ listed \ is \ in \ addition \ to \ and \ therefore \ not \ provided \ for \ by \ this \ quotation.$

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.