

Address: 202 Commerce Blvd, Lawrence , Pennsylvania , Phone: (724) 745-5300 Quotation: 15055 United States Q-754-S

To: Contractor Holder Bid Date: 2019-06-05

202 Commerce Blvd., Lawrence, Pennsylvania **Expiry Date:** 2019-07-05

15241 Creator: Drew Pomrenke ,
Attn.: N/A dpomrenke@jboconnor.com

Sales Rep.: Casey Devlin , cdevlin@jboconnor.com

Shipping Address: 301 Grant

Street, Pittsburgh, Pennsylvania, United

States

Job Name: Oxford Centre - 37th Floor Pittsburgh, PA

Engineer: CJL Engineering Architect: LGA Partners

724-745-5300

Comments:

Phone:

Section Brand: Sloan

| Label | Product No. Description | List Price | Qty. |
|-----------|--|------------|------|
| WC-1/WC-2 | ST-2459-STG | \$157.55 | 1 |
| | Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28 GPF, 1.6 GPF, and dual flush 1.6/1.1 GPF with 1-1/2" IPS top spud, with Sloan-Tec Hydrophobic antibacterial glaze (2172459) | | |
| | ECOS 111-1-6/1.1 HW | \$705.90 | 1 |
| | Sloan - Exposed, Hardwire, Sensor activated ECOS Hardwire Dual Flush Water Closet flushometer. 1.1/1.6 GPF. (3370420) | | |
| | EL-451 | \$103.80 | 1 |
| | Sloan - Box mount will operate up to 8 flush valves (0345125) | | |
| Note: P90 | 1 - Specifications - Fixture Schedule | | |
| WC-3 | ST-2029-A | \$160.65 | 1 |
| | Sloan - ADA Floor Mount Universal, Top Spud (2102029) | | |
| | ECOS 111-1-6/1.1 HW | \$705.90 | 1 |
| | Sloan - Exposed, Hardwire, Sensor activated ECOS Hardwire Dual Flush Water Closet flushometer. 1.1/1.6 GPF. (3370420) | | |
| | EL-451 | \$103.80 | 1 |
| | Sloan - Box mount will operate up to 8 flush valves (0345125) | | |
| Note: P90 | 1 - Specifications - Fixture Schedule | | |
| UR-1/UR-2 | SU-7009-A | \$178.45 | 1 |
| | Sloan - Universal Vitreous china, 3/4" top spud, small urinal. 0.125 to 0.5 GPF (1107009) | | |
| | ECOS 186-0.125 HW | \$705.90 | 1 |
| | Sloan - Flushometers, Urinal, Battery-powered 0.125 gpf/0.5 Lpf, override button, Activated Sensor (3370440) | | |
| | EL-451 | \$103.80 | 1 |
| | Sloan - Box mount will operate up to 8 flush valves (0345125) | | |
| | 1 - Specifications - Fixture Schedule ing urinal as alternate. | | |
| L-1 | SS-3021 | \$100.90 | 1 |

Sloan - White vitreous china, Undermount rectangular lavatory fixture. Front overflow, 21-5/8" \times 15-3/4" \times 8-1/4" (3873021)

| | EAF-200-LT | \$717.30 | 1 |
|--------------------|---|----------|---|
| | Sloan - Sensor activated, electronic hand washing faucet for pre-tempered water operation. 0.5 GPM Single supply. Less transformer (LT) (3335055) | | |
| | EAF-37 | \$110.10 | 1 |
| | Sloan - 6 VDC Box mount adapter, will serve up to 10 EAF faucets (0335037) | | |
| Note: Q Note: Q | P901 - Specifications - Fixture Schedule Duoting as alternate. Duoting lav with larger dimensions. Duoting faucet with 0.5 GPM in lieu of 1.5 GPM. | | |
| L-2 | SS-3106-STG | \$161.20 | 1 |
| | Sloan - 20x18 Wall Hung Ledgeback Lav - 1 Hole, w/SloanTec Glaze(3873176) | | |
| | EAF-200-LT | \$717.30 | 1 |
| | Sloan - Sensor activated, electronic hand washing faucet for pre-tempered water operation. 0.5 GPM Single supply. Less transformer (LT) (3335055) | | |
| | EAF-37 | \$110.10 | 1 |
| | | | |

Sloan - 6 VDC Box mount adapter, will serve up to 10 EAF faucets (0335037)

Note: P901 - Specifications - Fixture Schedule

Note: Quoting faucet as alternate with 0.5 GPM in lieu of 1.5 GPM.

Section Brand: Pioneer

| Label | Product No. Description | List Price | Qty. |
|-------|---|------------|------|
| MB-1 | 0054-ULERC-Q | \$171.00 | 1 |
| | Pioneer - SERVICE SINK-7-7/8" TO 8-1/8" LVR HDL RIGID SPT 1/4 TURN-ROUGH CP | | |
| | CS-65001 | \$60.50 | 1 |
| | Pioneer - ACCESSORY-STAINLESS STEEL MOP HANGER | | |
| | CS-65002 | \$44.60 | 1 |

Pioneer - ACCESSORY-HOSE BRACKET W/30" LONG HOSE

Note: P901 - Specifications - Fixture Schedule Note: Quoting lever handles in lieu of cross handles.

Section Brand: Powers

| Label | Product No. Description | List Price | Qty. | | |
|--|--|------------|------|--|--|
| ASSE 1070 | LFE480-10 | \$284.00 | 1 | | |
| Mixing Valve | Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish | | | | |
| Note: P001 - Detail 2 Note: Quoting as suggestion. | | | | | |
| L-2 | LFLM495-1 | \$312.00 | 1 | | |
| (mixing valve) | Powers - 1/2 LFLM495-1 | | | | |
| Note: P901 - Specifications - Fixture Schedule | | | | | |

Section Brand: Watts Drainage

Note: Quoting without mounting bracket.

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

| Label | Product No. Description | List Price | Qty. |
|---|--|------------|------|
| Water Hammer Arrestors (bellows type) | SS Series Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C) | | 1 |

| | SS-A | \$549.50 | 1 |
|---|---|------------|---|
| | Watts - 1-11 fixture units, 1/2" (13 mm) connection | | |
| | SS-B | \$1,119.00 | 1 |
| | Watts - 12-32 fixture units, 3/4" (19 mm) connection | | |
| | SS-C | \$1,672.00 | 1 |
| | Watts - 33-60, fixture units, 1" (25 mm) connection | | |
| | SS-D | \$4,191.00 | 1 |
| | Watts - 61-113 fixture units, 1" (25 mm) connection | | |
| | SS-E | \$4,731.50 | 1 |
| | Watts - 114-154 fixture units, 1" (25 mm) connection | | |
| | SS-F | \$5,815.00 | 1 |
| | Watts - 155-330 fixture units, 1" (25 mm) connection | | |
| Note: P101 | ! - Numbered Notes #4 | | |
| Water | LF15M2-DR Series | | 1 |
| Hammer Arrestors (piston type) | Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C) | | |
| | LF15M2-A-DR | \$175.00 | 1 |
| | Watts - 1-11 fixture units, 1/2" (13 mm) connection | | |
| | LF15M2-B-DR | \$335.50 | |
| | Watts - 12-32 fixture units, 3/4" (19 mm) connection | | |
| | LF15M2-C-DR | \$529.50 |] |
| | Watts - 33-60, fixture units, 1" (25 mm) connection | | |
| | LF15M2-D-DR | \$1,118.00 | |
| | Watts - 61-113 fixture units, 1" (25 mm) connection | | |
| | LF15M2-E-DR | \$1,391.00 | 1 |
| | Watts - 114-154 fixture units, 1" (25 mm) connection | | |
| | LF15M2-F-DR | \$1,656.00 | 1 |
| | Watts - 155-330 fixture units, 1" (25 mm) connection | | |
| Note: P101 | ! - Numbered Notes #4 | | |
| WC-1/WC-2 | ISCA-101-L/R | \$1,587.50 | 1 |
| | Watts - single, horizontal, cast iron fitting,left/right side outlet | | |
| | ISCA-101-D | \$2,967.00 | 1 |
| | Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support | | |
| | ISCA-121 | \$1,801.00 | 1 |
| | Watts - single, vertical, cast iron fitting | | |
| | ISCA-121-D | \$3,182.00 | |
| | Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts | | |
| | ISCA-131-L/R | \$2,105.50 | |
| | Watts - single, vertical, cast iron fitting, left/right side outlet | Ψ2,103.30 | • |

| | ISCA-131-D | \$3,479.50 | 1 |
|-------------------|--|------------|---|
| | Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support | | |
| Note: P901 | l - Specifications - Fixture Schedule | | |
| UR-1/UR-2 | CA-321 | \$839.00 | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware. | | |
| Note: P903 | 1 - Specifications - Fixture Schedule | | |
| L-2 | TCA-411 Series | | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| | TCA-411 | \$989.50 | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| | TCA-411-D | \$1,411.00 | 1 |
| | Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin | | |

Note: P901 - Specifications - Fixture Schedule

locking device.

NOTE: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.