



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-731-S

To:	Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241	Bid Date:	2019-05-09
Attn.:	N/A	Expiry Date:	2019-06-08
Phone:	724-745-5300	Creator:	Drew Pomrenke , dpomrenke@jboconnor.com
		Sales Rep.:	Casey Devlin , cdevlin@jboconnor.com
		Shipping Address:	, Towanda, Pennsylvania, United States

Job Name: Towanda State Police Station Towanda, PA

Engineer: Martarano Engineering Inc

Comments:

Section Brand: Sloan

Label	Product No. Description	List Price	Qty.
P-2/P-2A	SS-3003 Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$86.75	1
	ETF-600-LT Sloan - Sensor operated 4" center-set electronic hand washing faucet for tempered or hot/cold application. 0.5 GPM, Vandal resistant spray head. Includes back check. Less Transformer (LT) (3365055)	\$620.35	1
	ETF-233 Sloan - Plug in type transformer (Up to 2 faucets can be operated) (0365534)	\$33.30	1
<i>Note: P-3.0 - Plumbing Fixture Schedule</i>			
P-3/P-3A	SU-1009-A Sloan - Universal Vireous china, 3/4" top spud. 0.125, 0.25 and 0.5 GPF includes dome strainer. (1101009)	\$272.80	1
	Sloan 186-0.125 DPB Sloan - Exposed 3/4" top spud. 0.125 GPF, Dual By-Pass (DPB) (3782643)	\$202.95	1
<i>Note: P-3.0 - Plumbing Fixture Schedule</i>			

Section Brand: Elkay

Label	Product No. Description	List Price	Qty.
P-5	LRAD2522550 Elkay - 18 Gauge Stainless Steel 25' x 22' x 5.5' Single Bowl Top Mount Kitchen Sink	\$925.00	1
	LK99 Elkay - DRAIN	\$120.00	1
	LKD2439BHC Elkay - FAUCET ASSEMBLY	\$809.00	1
<i>Note: P-3.0 - Plumbing Fixture Schedule</i>			
<i>Note: Quoting depth of 5.5" as suggestion as depth not specified.</i>			
P-6	LRAD2522550 Elkay - 18 Gauge Stainless Steel 25' x 22' x 5.5' Single Bowl Top Mount Kitchen Sink	\$925.00	1
	LK99 Elkay - DRAIN	\$120.00	1

	LK1000CR	\$135.00	1
	Elkay - SINGLE LEVER KIT W/ ESC, CR		
Note: P-3.0 - Plumbing Fixture Schedule			
Note: Quoting depth of 5.5" as suggestion as depth not specified.			
Note: Specified faucet not found, quoting alternate faucet.			

P-8	EZSTL8LC	\$1,615.00	1
	Elkay - VERSATILE BI-LVL 8GPH LT GRY		
Note: P-3.0 - Plumbing Fixture Schedule			

Section Brand: Pioneer

Label	Product No. Description	List Price	Qty.
P-7	0054-ULE-Q Pioneer - SERVICE SINK-7-7/8" TO 8-1/8" LVR HDL RIGID SPT 1/4 TURN-PC	\$193.00	1
	CS-65001 Pioneer - ACCESSORY-STAINLESS STEEL MOP HANGER	\$60.50	1
	CS-65002 Pioneer - ACCESSORY-HOSE BRACKET W/30" LONG HOSE	\$44.60	1
Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications			
Note: Quoting faucet with lever handle in lieu of cross handles.			
Note: Quoting accessories as options.			

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
Thermostatic Mixing Valve	LFMM431-10 Powers - HydroGuard XP Thermostatic Series LFMM430	\$1,445.00	1
Note: P-1.0 - Water Heater Piping Diagram			
P-4	P905HM1000 Powers - Pressure Balancing Valve, 1/2" copper sweat connection, ABS faceplate with color-coded graphics, lever handle. CP finish, Deluxe, Chrome Plated Brass, Arm and Flange	\$326.00	1
Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications			
P-4A	P905HH101WY Powers - Pressure Balancing Valve, 1/2" copper sweat connection, Low Flow Shower (1.5 gpm), Arm & Flange, 24" Chrome ADA Wall Grab Bar System, Vacuum Breaker, in-line, Diverter, concealed, 1/2" IPS Metal Handle	\$1,054.00	1
Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications			
Note: Quoting as alternate.			
P-11 (mixing valve)	ETV200-13 Powers - HydroGuard Emergency Tempering Valve, with Cold Water Bypass, 3/4"x 1", Rough Bronze, with Temperature Pressure Gauge on Outlet	\$1,925.00	1
Note: P-3.0 - Plumbing Fixture Schedule			
Master Mixing Valve	LFSH1432-1 Powers - Hi-Lo Master Tempering Valve, 57 gpm, Rough Brass, Standard Finish, Standard 90 - 160°F (32 - 71°C)	\$3,649.00	1
Note: P-4.0 - Plumbing Specifications			
Lavatory Mixing Valve	LFE480-10 Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish	\$284.00	1
Note: P-4.0 - Plumbing Specifications			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
BFP 1 1/2"	LF009M2-QT : 1 1/2 Watts - Lead Free cast copper silicon alloy body for 1/4" to 2" and fused epoxy coated cast iron body for 2-1/2" and 3", replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules resilient seated isolation valves, resilient seated screw driver slotted test cocks, quarter turn ball-valves, 1-1/2"Ø (38 mm) pipe connection (0391006)	\$1,304.00	1
	909-AGC Watts - 909-AGC Air Gap (0881376)	\$106.50	1
	LF777SI : 1 1/2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/2"Ø (38 mm) valve (0379115)	\$213.00	1
Note: P-1.0 - Plumbing - Domestic Water Plan & P-1.0 - Water Service Entrance Piping Diagram			
BFP 1/2"	LF007-QT : 1/2 Watts - Lead Free cast copper silicon alloy body for 1/2" to 2" connections or fused epoxy coated cast iron body for 2-1/2" to 3" connections, replaceable seat and seat discs, resilient seated isolation valves, quarter turn ball-valves, 1/2"Ø (13 mm) pipe connection (0063230)	\$374.50	1
	LF777SI : 1/2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1/2"Ø (13 mm) valve (0379111)	\$68.25	1
Note: P-1.0 - Plumbing - Domestic Water Plan			
P-2/P-2A (mixing valve)	LFUSG-B-M2 Watts - Lead Free brass body construction, copper thermostat with stainless steel springs, integral checks and 40 mesh stainless steel screens, 4-port with cap for three port application, "H" pattern body, ASSE 1070 and cUPC, valve shall control temperature from a low of 1/4gpm, 3/8"Ø (10 mm) male compression (0204143)	\$297.50	1
Note: P-3.0 - Plumbing Fixture Schedule			
Hose Bibb	SC8-4 Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)	\$81.25	1
Note: P-4.0 - Plumbing Specifications Note: Quoting as suggestion.			
Expansion Tank	DETA 12 Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 5 gallons (0212027)	\$2,109.00	1
Note: P-4.0 - Plumbing Specifications			

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Label	Product No. Description	List Price	Qty.
Trap Primer	LFTP300-DR Series Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		1
	LFTP300T Watts - 1/2", Threaded Inlet and Outlet Connect	\$270.00	1
	LFTP300S Watts - 1/2", Soldered Inlet and Outlet Connect	\$270.00	1

	LFTP300-DU-DR	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
Note: P-1.0 - Trap Primer Diagram			
<i>Note: Quoting as alternate.</i>			
P-2	TCA-411 Series		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411	\$989.50	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411-D	\$1,411.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications			
P-3/P-3A	CA-321	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications			
P-4 (shower drain)	FD-1100-A5		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, stainless steel, round strainer		
	FD-1100-A5,2,3,4	\$601.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-1100-A5,6	\$721.50	1
	Watts - 6"Ø (152 mm)		
Note: P-3.0 - Plumbing Fixture Schedule			
<i>Note: Quoting as alternate, without surface membrane clamp.</i>			
P-8	CA-431-1	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications			
P-9	HY-440	\$665.50	1
	Watts - warm climate, heavy duty chrome plated bronze head, seat casting and internal working parts, wall mount, concealed, polished chrome plated face plate, vandal resistant integral vacuum breaker, loose key, 3/4"Ø (19 mm) male hose connection, 1" male threaded x 3/4" internal SWT 90° connection with 360° swivel.		
Note: P-3.0 - Plumbing Fixture Schedule			
P-10	HY-420-88		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, seat casting and internal working parts, wall mount, bronze wall casing, chrome plated face, integral vacuum breaker, loose key, wall clamp		
	HY-420-88,-4,-6,-8	\$864.50	1
	Watts - 4" (102 mm), 6" (152 mm), 8" (203 mm) thick		
	HY-420-88,-10,-12,-14	\$1,006.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		

	HY-420-88,-16,-18	\$1,147.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	Note: P-3.0 - Plumbing Fixture Schedule & P-4.0 - Plumbing Specifications		
	<i>Note: Quoting chrome finish in lieu of stainless steel.</i>		
FD-1	FD-100-FC7-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 7" (178 mm) diameter nickel bronze, adjustable round strainer, trap primer connection		
	FD-100-FC7-7,2,3,4	\$1,480.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-FC7-7,6	\$1,600.00	1
	Watts - 6"Ø (152 mm)		
	Note: P-3.0 - Plumbing Fixture Schedule		
FD-2	FD-320-Y-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 8" (203 mm) diameter, ductile iron grate, trap primer tapping		
	FD-320-Y-7,2,3,4	\$508.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-320-Y-7,6	\$628.00	1
	Watts - 6"Ø (152 mm)		
	Note: P-3.0 - Plumbing Fixture Schedule		
	<i>Note: Quoting as alternate.</i>		
FD-3	D-SS	\$672.00	1
	Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) no-hub bottom outlet(s), pre-sloped trench, 6" (152 mm) wide, including frame connectors, grate lockdowns and construction covers, ductile iron frame, framed anchored grate, stainless steel slotted, Class A		
	Note: P-3.0 - Plumbing Fixture Schedule		
	<i>Please note trench drain price is per foot.</i>		
	<i>Note: Quoting as alternate.</i>		
FD-3	CB-624-DI	\$1,344.00	1
(catch basin)	Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) and 6" (152 mm) no hub bottom outlets, 6" (152 mm) wide, 24" (610 mm) long, ductile iron grate, Class F		
	Note: P-3.0 - Plumbing Fixture Schedule		
	<i>Note: Quoting as alternate, ductile iron in lieu of stainless steel.</i>		
Water Hammer Arrestors	SS Series		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
	Note: P-4.0 - Plumbing Specifications		

Floor	CO-200-R-6		1
Cleanout	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top, vandal proof		
	CO-200-R-6,2	\$721.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-R-6,3	\$757.00	1
	Watts - 3"Ø (76 mm)		
	CO-200-R-6,4	\$977.00	1
	Watts - 4"Ø (102 mm)		
Note: P-4.0 - Plumbing Specifications			
Wall	CO-460-RD		1
Cleanout	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$364.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$417.50	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$611.50	1
	Watts - 4"Ø (102 mm)		
Note: P-4.0 - Plumbing Specifications			
Floor Drain	FD-100-A6		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" (152 mm) diameter, nickel bronze, round strainer		
	FD-100-A6,2,3,4	\$588.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-A6,6	\$708.50	1
	Watts - 6"Ø (152 mm)		

Note: P-4.0 - Plumbing Specifications

Note: Quoting as suggestion.

NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.