



**Address:** 202 Commerce Blvd, Lawrence , Pennsylvania ,  
15055 United States

**Phone:** (724) 745-5300

**Quotation:**  
**Q-845-S**

<b>To:</b>	<b>Contractor Holder</b> 202 Commerce Blvd., Lawrence, Pennsylvania 15241	<b>Bid Date:</b>	2019-08-02
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2019-09-01
<b>Phone:</b>	724-745-5300	<b>Creator:</b>	Drew Pomrenke , dpomrenke@jboconnor.com
		<b>Sales Rep.:</b>	Casey Devlin , cdevlin@jboconnor.com
		<b>Shipping Address:</b>	, Cranberry, Pennsylvania, United States

**Job Name: J.P. Morgan Chase RBC - Cranberry Twp, PA**

**Comments:**

**Section Brand: Sloan**

Label	Product No. Description	List Price	Qty.
LAV	<b>SS-3003</b> Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003)	\$86.75	1
	<b>EAFF-200-P-ISM</b> Sloan - Sensor activated, electronic hand washing faucet with integral spout temperature mixer for hot and cold water operation. 0.5 GPM Plug in transformer (3335051)	\$843.05	1

**Note:** P2.2 - Plumbing Fixture Schedule

*Note: Quoting transformer with faucet.*

**Section Brand: Elkay**

Label	Product No. Description	List Price	Qty.
SK	<b>LRAD202250MR2</b> Elkay - 18 Gauge Stainless Steel 19.5' x 22' x 5' Single Bowl Top Mount Kitchen Sink	\$890.00	1
	<b>LK99</b> Elkay - DRAIN	\$120.00	1
	<b>LK3000CR</b> Elkay - REMOTE HANDLE KIT FCT CR	\$254.00	1

**Note:** P2.2 - Plumbing Fixture Schedule

EWC	<b>EZSTL8WSSK</b> Elkay - BFS VERS BI-LVL 8GPH SS	\$2,427.00	1
-----	--	------------	---

**Note:** P2.2 - Plumbing Fixture Schedule

**Section Brand: Pioneer**

Label	Product No. Description	List Price	Qty.
MB	<b>0054-ULERC-Q</b> Pioneer - SERVICE SINK-7-7/8" TO 8-1/8" LVR HDL RIGID SPT 1/4 TURN-ROUGH CP	\$171.00	1
	<b>CS-65001</b> Pioneer - ACCESSORY-STAINLESS STEEL MOP HANGER	\$60.50	1
	<b>CS-65002</b> Pioneer - ACCESSORY-HOSE BRACKET W/30" LONG HOSE	\$44.60	1

**Note:** P2.2 - Plumbing Fixture Schedule

*Note: Quoting lever handles in lieu of cross handles.*

## Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
1 1/2" BFP	<b>LF009M2-QT : 1 1/2</b> Watts - Lead Free cast copper silicon alloy body for 1/4" to 2" and fused epoxy coated cast iron body for 2-1/2" and 3", replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules resilient seated isolation valves, resilient seated screw driver slotted test cocks, quarter turn ball-valves, 1-1/2"Ø (38 mm) pipe connection (0391006)	\$1,304.00	1
	<b>909-AGC</b> Watts - 909-AGC Air Gap (0881376)	\$106.50	1
	<b>LF777SI : 1 1/2</b> Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/2"Ø (38 mm) valve (0379115)	\$213.00	1

**Note:** P1.1 - Coded Notes #3 & P1,1- Plumbing Supply Piping Plan  
*Note: Quoting size as per line size on detail.*

## Section Brand: Watts Drainage

**Header:** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

Label	Product No. Description	List Price	Qty.
WHA (bellows type)	<b>SS Series</b> Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		1
	<b>SS-A</b> Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$549.50	1
	<b>SS-B</b> Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$1,119.00	1
	<b>SS-C</b> Watts - 33-60, fixture units, 1" (25 mm) connection	\$1,672.00	1
	<b>SS-D</b> Watts - 61-113 fixture units, 1" (25 mm) connection	\$4,191.00	1
	<b>SS-E</b> Watts - 114-154 fixture units, 1" (25 mm) connection	\$4,731.50	1
	<b>SS-F</b> Watts - 155-330 fixture units, 1" (25 mm) connection	\$5,815.00	1

**Note:** P1.1 - Coded Notes #7

WHA (piston type)	<b>LF15M2-DR Series</b> Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		1
	<b>LF15M2-A-DR</b> Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$175.00	1
	<b>LF15M2-B-DR</b> Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$335.50	1
	<b>LF15M2-C-DR</b> Watts - 33-60, fixture units, 1" (25 mm) connection	\$529.50	1
	<b>LF15M2-D-DR</b> Watts - 61-113 fixture units, 1" (25 mm) connection	\$1,118.00	1

	<b>LF15M2-E-DR</b>	\$1,391.00	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>LF15M2-F-DR</b>	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note: P1.1 - Coded Notes #7</b>			
FCO	<b>CO-200-R</b>		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	<b>CO-200-R,2</b>	\$625.50	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200-R,3</b>	\$661.00	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200-R,4</b>	\$881.00	1
	Watts - 4"Ø (102 mm)		
<b>Note: P2.1 - Floor Cleanout Detail</b>			
<i>Note: Quoting as suggestion as per detail.</i>			
Wall Cleanout	<b>CO-460-RD</b>		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	<b>CO-460-RD,2</b>	\$364.00	1
	Watts - 2"Ø (51 mm)		
	<b>CO-460-RD,3</b>	\$417.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-460-RD,4</b>	\$611.50	1
	Watts - 4"Ø (102 mm)		
<b>Note: P2.1 - Wall Cleanout Detail</b>			
<i>Note: Quoting as suggestion.</i>			
LAV	<b>TCA-411 Series</b>		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>TCA-411</b>	\$989.50	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>TCA-411-D</b>	\$1,411.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
<b>Note: P2.2 - Plumbing Fixture Schedule</b>			
EWC	<b>CA-431-1</b>	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
<b>Note: P2.2 - Plumbing Fixture Schedule</b>			
RHB	<b>HY-900</b>	\$3,159.50	1
	Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, roof hydrant with and lift handle and lock option, integral epoxy coated cast iron roof mounting plate with clamping collar, 1/8" NPT drain port		
<b>Note: P2.2 - Plumbing Fixture Schedule</b>			
<i>Note: Quoting as alternate.</i>			

HB	<b>HY-725-88</b>		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		
	<b>HY-725-88,-6,-8</b>	\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	<b>HY-725-88,-10,-12,-14</b>	\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	<b>HY-725-88,-16,-18</b>	\$1,830.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	<b>HY-725-88,-20,-22,-24</b>	\$1,870.00	1
	Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick		
	<b>Note: P2.2 - Plumbing Fixture Schedule</b>		
FD	<b>FD-100-M5-5-7</b>		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" x 5" (127 mm x 127 mm) nickel bronze, square strainer, sediment bucket, trap primer tapping		
	<b>FD-100-M5-5-7,2,3,4</b>	\$751.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>FD-100-M5-5-7,6</b>	\$871.00	1
	Watts - 6"Ø (152 mm)		
	<b>Note: P2.2 - Plumbing Fixture Schedule</b>		
FD (trap primer)	<b>LFTP300-DR Series</b>		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$270.00	1
	Watts - 1/2", Soldered Inlet and Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
	<b>Note: P2.2 - Plumbing Fixture Schedule</b>		
	<i>Note: Quoting as alternate.</i>		
RD1	<b>RD-300-D-F-L-K</b>		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387mm) diameter, underdeck clamp, adjustable extension flange, vandal proof dome, ductile iron dome		
	<b>RD-300-D-F-L-K,2,3,4</b>	\$1,941.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-300-D-F-L-K,5,6</b>	\$2,244.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	<b>RD-300-D-F-L-K,8,10</b>	\$2,546.50	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
	<b>Note: P2.2 - Plumbing Fixture Schedule</b>		
RD2/OD2 (opt 1)	<b>RD-240</b>		1
	Watts - 6-1/8" (156 mm) diameter cast iron body, flashing clamp, 5-1/8" (130 mm), cast nickel bronze dome strainer		
	<b>RD-240,2,3,4</b>	\$619.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>Note: P2.2 - Plumbing Fixture Schedule</b>		

RD2 (opt 2 & 3)	<b>RD-230</b> Watts - 6-1/8" (156 mm) diameter cast iron body, flashing clamp, side IPS threaded outlet, 5-1/8" (130 mm), cast nickel bronze dome strainer		1
	<b>RD-230,2,3,4</b> Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$739.50	1
<b>Note:</b> P2.2 - Plumbing Fixture Schedule <i>Note: Quoting as alternate with side outlet only.</i>			
OD1	<b>RD-300-D-F-L-R-K</b> Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, deck flange/adj.extension,2" External Water dam		1
	<b>RD-300-D-F-L-R-K,2,3,4</b> Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$2,172.00	1
	<b>RD-300-D-F-L-R-K,5,6</b> Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size	\$2,474.50	1
	<b>RD-300-D-F-L-R-K,8,10</b> Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size	\$2,777.00	1
<b>Note:</b> P2.2 - Plumbing Fixture Schedule			
DN1	<b>RD-940-83</b> Watts - cast nickel bronze, anchor flange and pre-drilled counter-sunk mounting holes, no hub, stainless steel bird screen		1
	<b>RD-940-83,3,4</b> Watts - 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$1,633.00	1
	<b>RD-940-83,5,6</b> Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size	\$2,165.00	1
	<b>RD-940-83,8</b> Watts - 8"Ø (203 mm)	\$3,204.00	1
<b>Note:</b> P2.2 - Plumbing Fixture Schedule			
GCO/WCO	<b>CO-380-RD</b> Watts - cast iron body counter sunk, brass plug, round, stainless steel access cover and stainless steel vandal proof screw		1
	<b>CO-380-RD,2</b> Watts - 2"Ø (51 mm)	\$232.00	1
	<b>CO-380-RD,3</b> Watts - 3"Ø (76 mm)	\$286.00	1
	<b>CO-380-RD,4</b> Watts - 4"Ø (102 mm)	\$343.50	1
	<b>CO-380-RD,6</b> Watts - 6"Ø (152 mm)	\$727.00	1

**Note:** P2.2 - Plumbing Fixture Schedule

*Note: Quoting as alternate.*

**NOTE :** \*\*\*NOTE: Watts Drainage does not meet PA.DGS please be advised\*\*\*

**Special Terms:**

All pricing is plus freight unless Mfr freight terms are met.

Pricing good for 30 days.

Pricing subject to change if Mfr pricing changes.

**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.

