



Address: 202 Commerce Blvd, Lawrence , Pennsylvania ,
15055 United States

Phone: (724) 745-5300

Quotation:
Q-156-S-1

| | | | |
|---------------|---|--------------------------|---|
| To: | Contractor Holder 202 Commerce Blvd., Lawrence, Pennsylvania 15241 | Bid Date: | 2019-08-28 |
| Attn.: | N/A | Expiry Date: | 2019-09-27 |
| Phone: | 724-745-5300 | Creator: | Drew Pomrenke , dpomrenke@jboconnor.com |
| | | Sales Rep.: | Casey Devlin , cdevlin@jboconnor.com |
| | | Shipping Address: | 350 Technology Dr. 15219, Pittsburgh, Pennsylvania, United States |

Job Name: The Riviera at PTC

Engineer: Allen & Shariff Engineering **Architect:** NEXT Architecture

Comments:

Section Brand: Sloan

| Label | Product No. Description | List Price | Qty. |
|---|--|------------|------|
| WC-1 /WC-2 | ST-2459-BPL Sloan - Vitreous China, ADA compliant water closet bowl only, 1.28, 1.6 GPF and dual flush 1.6/1.1 GPF wall hung elongated bowl with 1-1/2" IPS top spud. Bed pan lugs (BPL) (2112059) | \$151.70 | 1 |
| | G2 OPTIMA PLUS 8111 Sloan - Battery powered, sensor activated, 1 1/2" top spud, exposed closet flushometer. Requires no AC hookups, uses four AA batteries. Metal cover 1.6 GPF (3250400) | \$637.25 | 1 |
| <i>Note: P0.02 - Plumbing Fixture Schedule</i> | | | |
| WC-3 | ST-2229-A Sloan - ADA Floor Mount Rear Outlet Universal, Top Spud (2112029) | \$465.95 | 1 |
| | G2 OPTIMA PLUS 8111 Sloan - Battery powered, sensor activated, 1 1/2" top spud, exposed closet flushometer. Requires no AC hookups, uses four AA batteries. Metal cover 1.6 GPF (3250400) | \$637.25 | 1 |
| <i>Note: P0.02 - Plumbing Fixture Schedule</i> | | | |
| U-1/U-2 | SU-7006-A Sloan - Universal Vitreous china, 3/4" top spud, small urinal. 1.0 GPF (1107006) | \$178.45 | 1 |
| | G2 8180-1 Sloan - Flushometers, Urinal, Battery-powered 1 gpf/3.8 Lpf, Activated Sensor (3250406) | \$637.25 | 1 |
| <i>Note: P0.02 - Plumbing Fixture Schedule</i> | | | |
| L-1 | EFX377.000.0200 Sloan - Basys Solar powered, sensor activated, LCD Solar, Integral side mixer, 1.5 GPM laminar flow, for pre-tempered or hot and cold water operations. (3324256) | \$1,335.70 | 1 |
| <i>Note: Addendum 8 - P0.02 - Plumbing Fixture Schedule; Quoting based on model, description and website specifications. Note: No Equal Alternate for Basin by Sloan.</i> | | | |
| L-2 | SS-3003 Sloan - Vitreous china wall mounted lavatory with backsplash, 4" centers, overflow, ADA compliant, 21" x 19.25" (3873003) | \$86.75 | 1 |
| | EBF-650 Sloan - Battery powered, chrome plated brass sensor operated 4" center-set electronic hand washing faucet for tempered or hot/cold water. .5 GPM vandal resistant spray head. (3315025) | \$759.70 | 1 |

*Note: Addendum 8 - P0.02 - Plumbing Fixture Schedule
Note: Model specified for lav not found quoting model as a suggestion.*

| | | | |
|---|----------------|----------|---|
| S-1/S-2 | SF-2350 | \$458.50 | 1 |
| Sloan - Sensor activated, electronic, 4" centerset hand washing faucet for tempered or hot/cold water operation. Battery operated 0.5 GPM (3362119) | | | |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| Note: Quoting as per model specified, lavatory sensor faucet. | | | |

Section Brand: Elkay

| Label | Product No. Description | List Price | Qty. |
|---|--|------------|------|
| S-1 | ELUH1814 Elkay - 18 Gauge Stainless Steel 20.5' x 16.5' x 7.875' Single Bowl Undermount Kitchen Sink | \$622.00 | 1 |
| | LK99 Elkay - DRAIN | \$120.00 | 1 |
| Note: Addendum 8 - P0.02 - Plumbing Fixture Schedule | | | |
| Note: Quoting as alternate with larger dimensions (20.5'x16.5' in lieu of 18.5'x15.75') | | | |
| S-2 | ELUH231710 Elkay - 18 Gauge Stainless Steel 25.5' x 19.25' x 10' Single Bowl Undermount Kitchen Sink | \$796.00 | 1 |
| | LK99 Elkay - DRAIN | \$120.00 | 1 |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| Note: Quoting sink dimensions of 25'x19.25' in lieu of specified 25'x17.5' | | | |
| S-3 | 14-3C18X24-2-18X Elkay - Standard Scullery Sink, 3-Compartment 14" Deep Bowl(s), 18" Left & Right Drainboards, 94 (L) X 29.75 (W) X 43.75 (H) Over All | \$2,615.00 | 1 |
| Note: Addendum 8 - P0.02 - Plumbing Fixture Schedule | | | |
| EWC-1 | LZSTL8WSVRLK Elkay - BFS VERS BI-LVL FILTRD VR-BUB LT GRY | \$2,544.00 | 1 |
| Note: P0.02 - Plumbing Fixture Schedule; | | | |

Section Brand: Pioneer

| Label | Product No. Description | List Price | Qty. |
|--|--|------------|------|
| S-3 | 0047-ULE3 Pioneer - KITCHEN-WALLMOUNT 7-7/8" TO 8-1/8" LVR HDL 12" TUBE SPT-PC | \$143.00 | 1 |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| Note: Quoting 1.5 GPM in lieu of 2.2 GPM. | | | |
| MB-1 | 0054-ULERC-Q Pioneer - SERVICE SINK-7-7/8" TO 8-1/8" LVR HDL RIGID SPT 1/4 TURN-ROUGH CP | \$171.00 | 1 |
| | CS-65001 Pioneer - ACCESSORY-STAINLESS STEEL MOP HANGER | \$60.50 | 1 |
| | CS-65002 Pioneer - ACCESSORY-HOSE BRACKET W/30" LONG HOSE | \$44.60 | 1 |
| Note: P0.02 - Plumbing Fixture Schedule | | | |

Section Brand: Powers

| Label | Product No. Description | List Price | Qty. |
|---|---|------------|------|
| MV-1 | LFSH1434-13 Powers - HydroGuard Hi/Lo Master Tempering Valve - 127 gpm, Rough brass, Standard, T/P Gauge on outlet, Rough Brass | \$5,574.00 | 1 |
| Note: P0.01 - Mixing Valve and Pressure Regulator Schedule | | | |

| | | | |
|---|--|------------|---|
| MV-2 | LFLM495-1 Powers - 1/2 LFLM495-1 | \$312.00 | 1 |
| Note: P0.01 - Mixing Valve and Pressure Regulator Schedule Note: Wall mounting by others. | | | |
| SH-1 | P910HH1U00 Powers - Biltmore Series 900 Pressure Balancing Valves | \$466.00 | 1 |
| Note: Addendum 8 - P0.02 - Plumbing Fixture Schedule Note: Quoting as alternate. | | | |
| SH-2 | P910HH10LWY Powers - Pressure Balancing Valves, 1/2" Copper sweat connections, Low Flow Shower (1.5 gpm), Low Flow (1.5 gpm), Metal Hose, 30" Glide Rail, in-line Vacuum Breaker, Diverter, Concealed, 1/2" IPS Metal Handle | \$1,152.00 | 1 |
| Note: Addendum 8 - P0.02 - Plumbing Fixture Schedule | | | |

Section Brand: Watts Regulators

| Label | Product No. Description | List Price | Qty. |
|--|---|------------|------|
| ET-1 | DETA 5 Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 3.5 gallons (0212026) | \$1,832.00 | 1 |
| Note: P0.01 - Water Heater Schedule | | | |
| BP-1 | 994-OSY : 4 Watts - thermoplastic construction with stainless steel hinge pins, cam arm and cam bearing, 300 series stainless steel body stainless steel differential relief valve with rolling diaphragm, bottom mounted, resilient seated shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 4"Ø (102 mm) pipe connection (0438049) | \$6,348.00 | 1 |
| | 994-AGKP Watts - 994-AGKP Air Gap | \$296.50 | 1 |
| | 77F-DI-FDA-125 : 4 Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 4"Ø (102 mm) valve (0825212) | \$1,042.00 | 1 |
| Note: Addendum 8 - P0.01 - Backflow Preventer Schedule & P5.01 - Domestic Water Riser; Incoming Water Service | | | |
| BP-1 Opt. | 957-OSY : 4 Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 4"Ø (102 mm) pipe connection (0111586) | \$5,200.00 | 1 |
| | 957-AG Watts - 957-AG Air Gap (0111764) | \$269.50 | 1 |
| | 77F-DI-FDA-125 : 4 Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 4"Ø (102 mm) valve (0825212) | \$1,042.00 | 1 |
| Note: Addendum 8 - P0.01 - Backflow Preventer Schedule & P5.01 - Domestic Water Riser; Incoming Water Service | | | |
| BP-3 | SD2-MF : 1/4 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061651) | \$170.50 | 1 |

| | | |
|--|----------|---|
| SD2-MF : 3/8 | \$180.50 | 1 |
| Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655) | | |

Note: P0.01 - Backflow Preventer Schedule

Section Brand: Watts Drainage

Header: ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

| Label | Product No. Description | List Price | Qty. |
|-------|--|------------|------|
| SA | LF15M2-DR Series Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C) | | 1 |
| | LF15M2-A-DR Watts - 1-11 fixture units, 1/2" (13 mm) connection | \$175.00 | 1 |
| | LF15M2-B-DR Watts - 12-32 fixture units, 3/4" (19 mm) connection | \$335.50 | 1 |
| | LF15M2-C-DR Watts - 33-60, fixture units, 1" (25 mm) connection | \$529.50 | 1 |
| | LF15M2-D-DR Watts - 61-113 fixture units, 1" (25 mm) connection | \$1,118.00 | 1 |
| | LF15M2-E-DR Watts - 114-154 fixture units, 1" (25 mm) connection | \$1,391.00 | 1 |
| | LF15M2-F-DR Watts - 155-330 fixture units, 1" (25 mm) connection | \$1,656.00 | 1 |

Note: P0.01 - Shock Arrestor Schedule

| | | | |
|------|---|----------|---|
| FD-1 | FD-100-M6-7 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" x 6" (152 mm x 152 mm) nickel bronze, square strainer, trap primer connection | | 1 |
| | FD-100-M6-7,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | \$716.50 | 1 |
| | FD-100-M6-7,6 Watts - 6"Ø (152 mm) | \$836.50 | 1 |

Note: P0.01 - Drain and Hose Bibb Schedule

| | | | |
|------|--|----------|---|
| FD-2 | FD-310 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 7" (178 mm) diameter, ductile iron grate | | 1 |
| | FD-310,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | \$437.00 | 1 |
| | FD-310,6 Watts - 6" (152 mm) pipe size" (19 mm) outlet | \$557.00 | 1 |

Note: P0.01 - Drain and Hose Bibb Schedule

| | | | |
|------|--|------------|---|
| HB-1 | HY-725 Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door | | 1 |
| | HY-725,-6,-8 Watts - 6" (152 mm), 8" (203 mm) thick | \$1,547.00 | 1 |

| | | | |
|--|--|------------|---|
| | HY-725,-10,-12,-14 | \$1,690.00 | 1 |
| | Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick | | |
| | HY-725,-16,-18 | \$1,830.00 | 1 |
| | Watts - 16" (406 mm), 18" (457 mm) thick | | |
| | HY-725,-20,-22,-24 | \$1,870.00 | 1 |
| | Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick | | |
| Note: P0.01 - Drain and Hose Bibb Schedule | | | |
| RD-1 | RD-300-D-F-K80 | | 1 |
| | Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, aluminum dome, underdeck clamp, adjustable extension flange | | |
| | RD-300-D-F-K80,2,3,4 | \$1,852.00 | 1 |
| | Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | | |
| | RD-300-D-F-K80,5,6 | \$2,154.00 | 1 |
| | Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size | | |
| | RD-300-D-F-K80,8,10 | \$2,457.00 | 1 |
| | Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size | | |
| Note: P0.01 - Drain and Hose Bibb Schedule | | | |
| RD-2 | RD-300-D-F-W-K80 | | 1 |
| | Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp and 4" (102 mm) high internal stand pipe, no-hub outlet, 15-1/4" (387 mm) diameter, aluminum dome, underdeck clamp, adjustable extension flange | | |
| | RD-300-D-F-W-K80,2,3,4 | \$2,275.00 | 1 |
| | Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | | |
| | RD-300-D-F-W-K80,5,6 | \$2,577.50 | 1 |
| | Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size | | |
| | RD-300-D-F-W-K80,8,10 | \$2,880.00 | 1 |
| | Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size | | |
| Note: P0.01 - Drain and Hose Bibb Schedule | | | |
| RD-3 | RD-100-CP-D | | 1 |
| | Watts - 14-1/8" (359 mm) diameter cast iron body, flashing clamp, no-hub outlet, 12-3/4" x 12-3/4" (324 mm x 324 mm) square, ductile iron grate, underdeck clamp | | |
| | RD-100-CP-D,2,3,4 | \$1,323.00 | 1 |
| | Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | | |
| | RD-100-CP-D,5,6 | \$1,323.00 | 1 |
| | Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size | | |
| Note: P0.01 - Drain and Hose Bibb Schedule; Please be advised model is not available w/ Aluminum top. | | | |
| RH-1 | HY-900 | \$3,159.50 | 1 |
| | Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, roof hydrant with and lift handle and lock option, integral epoxy coated cast iron roof mounting plate with clamping collar, 1/8" NPT drain port | | |
| Note: P0.01 - Drain and Hose Bibb Schedule | | | |
| <i>Note: Quoting as alternate.</i> | | | |
| FS-1 | FS-730-1-7-128 | | 1 |
| | Watts - cast iron body, 6-1/4" (159 mm) deep, no-hub outlet, polypropylene dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, nickel bronze top, trap primer connection, Grate with 2 1/2"(64) Center Opening | | |
| | FS-730-1-7-128,2,3,4 | \$3,237.50 | 1 |
| | Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size | | |

Note: Addendum 8 - P0.01 - Drain and Hose Bibb Schedule

| | | | |
|------|---|------------|---|
| CO-1 | CO-200-R-6 | | 1 |
| | Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top, vandal proof | | |
| | CO-200-R-6,2 | \$721.50 | 1 |
| | Watts - 2"Ø (51 mm) | | |
| | CO-200-R-6,3 | \$757.00 | 1 |
| | Watts - 3"Ø (76 mm) | | |
| | CO-200-R-6,4 | \$977.00 | 1 |
| | Watts - 4"Ø (102 mm) | | |
| | Note: P0.01 - Cleanout Schedule | | |
| | CARPET CLAMPING FLANGE (-CF) = \$285.00 LIST ADDER | | |
| | CARPET MARKER (-RC) = \$78.00 LIST ADDER | | |
| | NB HEAVY DUTY (-RX) = \$155.00 LIST ADDER | | |
| | TILE RECESS (-T) = NO ADDITIONAL | | |
| | TERRAZZO RECESS (-U) = \$354.00 LIST ADDER | | |
| CO-2 | CO-380-RD | | 1 |
| | Watts - cast iron body counter sunk, brass plug, round, stainless steel access cover and stainless steel vandal proof screw | | |
| | CO-380-RD,2 | \$232.00 | 1 |
| | Watts - 2"Ø (51 mm) | | |
| | CO-380-RD,3 | \$286.00 | 1 |
| | Watts - 3"Ø (76 mm) | | |
| | CO-380-RD,4 | \$343.50 | 1 |
| | Watts - 4"Ø (102 mm) | | |
| | CO-380-RD,6 | \$727.00 | 1 |
| | Watts - 6"Ø (152 mm) | | |
| | Note: P0.01 - Cleanout Schedule | | |
| CO-3 | CO-380 | | 1 |
| | Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug | | |
| | CO-380,2 | \$96.25 | 1 |
| | Watts - 2"Ø (51 mm) | | |
| | CO-380,3 | \$148.50 | 1 |
| | Watts - 3"Ø (76 mm) | | |
| | CO-380,4 | \$205.50 | 1 |
| | Watts - 4"Ø (102 mm) | | |
| | CO-380,6 | \$420.50 | 1 |
| | Watts - 6"Ø (152 mm) | | |
| | Note: P0.01 - Cleanout Schedule | | |
| CO-4 | CO-300-MF | \$1,390.50 | 1 |
| | Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top | | |
| | CO-380 | | 1 |
| | Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug | | |
| | CO-380,2 | \$96.25 | 1 |
| | Watts - 2"Ø (51 mm) | | |
| | CO-380,3 | \$148.50 | 1 |
| | Watts - 3"Ø (76 mm) | | |
| | CO-380,4 | \$205.50 | 1 |
| | Watts - 4"Ø (102 mm) | | |

| | | | |
|--|---|-------------|---|
| | CO-380,6 | \$420.50 | 1 |
| | Watts - 6"Ø (152 mm) | | |
| Note: P0.01 - Cleanout Schedule | | | |
| WC-1 /WC-2 | ISCA-101-L/R | \$1,587.50 | 1 |
| | Watts - single, horizontal, cast iron fitting, left/right side outlet | | |
| | ISCA-101-D | \$2,967.00 | 1 |
| | Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support | | |
| | ISCA-121 | \$1,801.00 | 1 |
| | Watts - single, vertical, cast iron fitting | | |
| | ISCA-121-D | \$3,182.00 | 1 |
| | Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts | | |
| | ISCA-131-L/R | \$2,105.50 | 1 |
| | Watts - single, vertical, cast iron fitting, left/right side outlet | | |
| | ISCA-131-D | \$3,479.50 | 1 |
| | Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support | | |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| U-1 /U-2 | CA-321 | \$663.00 | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware. | | |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| L-2 | TCA-411 Series | | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| | TCA-411 | \$989.50 | 1 |
| | Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| | TCA-411-D | \$1,411.00 | 1 |
| | Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device. | | |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| EWC-1 | CA-431-1 | \$1,214.50 | 1 |
| | Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware. | | |
| Note: P0.02 - Plumbing Fixture Schedule | | | |
| GI-1 | WD-35-L | \$11,240.00 | 1 |
| | Watts - steel, removable baffle assembly, skid-proof cover, secured with hex head center bolts, external cast iron flow control fitting, deep seal trap with cleanout, no-hub connections, flow rate of 35 GPM | | |

Note: Addendum 8 - P0.02 - Grease Interceptor Schedule

Extension up to 12" = \$3967.50

Extension over 12" add per inch = \$279.50

| | | | |
|----|--|----------|---|
| TP | LFTP300-DR Series | | 1 |
| | Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap | | |
| | LFTP300T | \$270.00 | 1 |
| | Watts - 1/2", Threaded Inlet and Outlet Connect | | |
| | LFTP300S | \$270.00 | 1 |
| | Watts - 1/2", Soldered Inlet and Outlet Connect | | |
| | LFTP300-DU-DR | \$189.00 | 1 |
| | Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit | | |

Note: P4.01 - Trap Seal Primer Details

| | | | |
|-------|---|----------|---|
| WCO-1 | CO-460-RD | | 1 |
| | Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw | | |
| | CO-460-RD,2 | \$364.00 | 1 |
| | Watts - 2"Ø (51 mm) | | |
| | CO-460-RD,3 | \$417.50 | 1 |
| | Watts - 3"Ø (76 mm) | | |
| | CO-460-RD,4 | \$611.50 | 1 |
| | Watts - 4"Ø (102 mm) | | |

Note: P4.01 - Wall Cleanouts Detail

| | | | |
|-------|--|----------|---|
| WCO-2 | CO-300-S7 | \$604.00 | 1 |
| | Watts - scoriated, square, access cover, nickel bronze, concealed mounting flanges, 7" (148 mm) square | | |
| | CO-460 | | 1 |
| | Watts - cast iron stack, no-hub outlet, counter sunk brass plug | | |
| | CO-460,2 | \$228.00 | 1 |
| | Watts - 2"Ø (51 mm) | | |
| | CO-460,3 | \$284.00 | 1 |
| | Watts - 3"Ø (76 mm) | | |
| | CO-460,4 | \$441.00 | 1 |
| | Watts - 4"Ø (102 mm) | | |

Note: P4.01 - Wall Cleanouts Detail

NOTE : ***NOTE: Watts Drainage does not meet PA.DGS please be advised***

Special Terms:

NOTE: Watts Drainage does not meet PA.DGS please be advised
 All pricing is plus freight unless Mfr freight terms are met.
 Pricing good for 30 days.
 Pricing subject to change if Mfr pricing changes.

Terms

Above prices are net.
 All taxes are extra.
 Partial or expedited shipments, at customer request, may result in additional freight charges.
 Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.
 Please ensure that all quoted product meets your projects specifications.
 Our company will only be responsible for products shown on the attached quotation.